



GENMAC Combi RG7300HEO-M5 GENERATOR 7,1KVA

Product price:

1,599.00 € tax excluded

Product description:

GENMAC Combi RG7300HEO-M5 GENERATOR 7,1KVA

The generator Genmac Combi RG7300HEO-M5 single phase has a Honda GX 390 Stage V gasoline powered engine capable of delivering a power of 7,1KVA with the possibility of connection to optional AVR.

The Genmac RG7300HEO-M5 single phase generator is equipped with a Honda engine powered by gasoline with a tank capacity of 6.1 liters for an autonomy of about three and a half hours, complete with elettric starter.

The generator is very light and makes it very easy to move for other uses, in addition for an even easier and more dynamic portability is possible the optional supply of a practical transport kit dedicated to this line of generators.

The Genmac 7,1KVA generator is portable of professional quality and you can ask for the supply with AVR.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

Technical features of generator 7,1KVA Genmac Combi RG7300HEO-M5



Power Supply: Gasoline

Boosting: Electric

Phase Type: Single Phase

Continuous Power: 6.4KVA / 5.8KW Maximum Power: 7.1KVA / 6.4KW

Motor: Honda GX390

Emission Standard: Stage V

Voltage: 230V Frequency: 50 Hz

3000 rpm

Fuel tank: 25 Lt.

Run time @ 75%: 12 h fixed rpm

Starting: Manual

Acoustic power: 72 dB (A) @ 7 m

Length (mm): 780 Width (mm): 540 Height (mm): 560 Dry weight (Kg): 96

If you are looking for another product then you can consult on <u>our catalog</u> other <u>terrestrial</u> <u>generator</u>.

Images and technical data are not binding and may be subject to review

Product features:

Phase: Single phase

Maximum power single phase (KW): 6.4 Continuous power single phase (KW): 5.8 Maximum power single phase (KVA): 7.1 Continuous power single phase (KVA): 6.4

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230

Engine: Honda GX390

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Electric

Cooling: Air

Fuel tank capacity (L): 25 Running time (h): 12



Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 780 Width (mm): 540 Height (mm): 560 Dry weight (Kg): 96

Product type: Generator ATS Switch device: No

Voltage regulator: AVR (optional)

