



# GENMAC Combiplus RG14000HEO-E5 GENERATOR 15,6KVA

**Product price:** 

3,090.00 € tax excluded

## **Product description:**

## **GENMAC Combiplus RG14000HEO-E5 GENERATOR 15,6KVA**

The **generator Genmac Combiplus RG14000HEO-E5** single phase has a Honda gasoline powered engine capable of delivering a power of 15,6KVA with the possibility of connection to optional AVR.

The GENMAC Combiplus RG14000HEO-E5 generator is equipped with a Honda Stage V engine certified for mobile use in the EU, but which does not comply with others criteria of the regulation. The engine is powered by gasoline by means of a tank with a capacity of 19 liters for an autonomy of about three and a half hours, complete with electric starter.

The Genmac 15,6KVA generator is equipped with a front control panel for portable units, with manual start and oil level sensor, with the possibility of modification by the customer with the optional remote control panel.

In combination with the generator it is possible to request the handling kit specifically designed for the selected model, for a more comfortable transport before the installation on the working lug.

The 15,6KVA generator is equipped with capacitor voltage regulator, on request it is possible to supply it with AVR voltage regulator.

### **Optional AVR regulator**

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use



the various devices connected, improving their performance and durability.

Technical features of generator 15,6KVA Genmac Combiplus RG14000HEO-E5

Power supply: Gasoline

Firing: Electric

Phase type: Single-phase

Continuous power: 14,2KVA / 12,8KW Maximum power: 15,6KVA / 14,0KW

Motor: Honda iGX800

Emissions regulation: Non-emissioned

Voltage: 230V Frequency: 50 Hz

3000 rpm Tank: 19 Lt.

Autonomy @ 75%: 3.6 h fixed rpm

Boosting: Manual Length (mm): 840 Width (mm): 620 Height (mm): 690 Dry weight (Kg): 175

If you are looking for another product then you can consult on our catalog other <u>terrestrial genegroups</u>.

Images and technical data are not binding and may be subject to review

#### **Product features:**

Phase: Single phase

Maximum power single phase (KW): 14 Continuous power single phase (KW): 12,8 Maximum power single phase (KVA): 15.6 Continuous power single phase (KVA): 14.2

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230 Engine: 4 Tempi

Engine rpm (rpm): 3000 Starting system: Elettrico

Cooling: Air

Fuel tank capacity (L): 19 Running time (h): 3.6



Length (mm): 870
Width (mm): 620
Height (mm): 690
Dry weight (Kg): 164
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR (optional)

