



GENMAC Combiplus G18000HEO-E5 GENERATOR 17,5KVA

Product description:

GENMAC Combiplus G18000HEO-E5 GENERATOR 17,5KVA

The **generator Genmac Combiplus G18000HEO-E5** single phase has a Honda gasoline powered engine capable of delivering a power of 17,5KVA with the possibility of connection to optional AVR.

The GENMAC Combiplus G18000HEO-E5 generator is equipped with a Honda Stage V engine certified for mobile use in the EU, but which does not comply with others criteria of the regulation. The engine is powered by gasoline by means of a tank with a capacity of 19 liters for an autonomy of about three and a half hours, complete with electric starter.

The Genmac 17,5KVA generator is equipped with a front control panel for portable units, with manual start and oil level sensor, with the possibility of modification by the customer with the optional remote control panel.

In combination with the generator it is possible to request the handling kit specifically designed for the selected model, for a more comfortable transport before the installation on the working lug.

The 17,5KVA generator is equipped with compound voltage regulator, on request it is possible to supply it with AVR voltage regulator.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use



the various devices connected, improving their performance and durability.

Technical features of generator 17,5KVA Genmac Combiplus G18000HEO-E5

Power Supply: Gasoline

Firing: Electric

Phase Type: Single Phase / Three Phase

Single Phase Continuous Power: 5.3 KVA / 4.8 KW

Maximum Single Phase Power: 5.8 KVA / 5.2 KW

Three Phase Continuous Power: 16.0KVA / 12.8KW

Maximum Three Phase Power: 17.5KVA / 14. 0KW

Motor: iGX800

Socket panel: 1 x 16A 230V - 1 x 32 A 400 V

Voltage: 230 / 400V

Frequency: 50 Hz

3000 rpm

Tank: 19 Lt.

Autonomy @ 75%: 3,6 h fixed rpm

Starting: Manual

Length (mm): 870

Width (mm): 620

Height (mm): 690

Dry weight (Kg): 166

If you are looking for another product then you can consult on our catalog other terrestrial generator.

Images and technical data are not binding and may be subject to review

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 5.2

Continuous power single phase (KW): 4.8

Maximum power single phase (KVA): 5.8

Continuous power single phase (KVA): 5.3

Maximum power three phase (KW): 14

Continuous power three phase (KW): 12.8

Maximum power three phase (KVA): 17.5

Continuous power three phase (KVA): 16

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400





Engine: 4 stroke
Engine rpm (rpm): 3000
Starting system: Electric
Cooling: Air
Fuel tank capacity (L): 19
Running time (h): 3.6
Length (mm): 870
Width (mm): 620
Height (mm): 690
Dry weight (Kg): 166
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR (optional)