



GENMAC Combipro RG5000HC-M5 GENERATOR 5,1KVA

Product price:

1.363,00 € tax excluded

Product description:

GENMAC COMBIPRO RG5000HC-M5 SINGLE-PHASE GENERATOR 5,1KVA

The generator Genmac Combipro RG5000HC-M5 single phase is equipped with a Honda Stage V gasoline powered engine capable of delivering a power of 5,1KVA with capacitor voltage regulator (AVR optional).

The Generators of the **Genmac Combipro RG5000 series** are among the most **silent** in their category, thanks to the side closing panels and the oversized muffler. The panels are covered with a **silent** silent material in polyester, this material is recyclable, washable, class 1, fire retardant and self-extinguishing.

These power generators are built with a **compact and robust** structure with sturdy **wheels and handle** integrated into the frame, which makes them handy and easily transportable. The 300mm diameter wheels with double reinforcement, with which Combipro generators are equipped, are integrated in the structure and the retractable handle can be folded to avoid unnecessary hindrance when not in use. On the frontal part there is also a full length support to avoid sinking into the ground.

The Genmac RG5000 5,1KVA generators are equipped with a **25-liter tank** with a large cap that is convenient to unscrew even with work gloves, filter and **fuel level indicator**. There is also a manual fuel circuit shut-off tap to prevent fuel leakage.

The Genmac Combipro mounts a **Honda OHV 4-stroke petrol engine**. They are very reliable engines that guarantee efficient combustion and **low fuel consumption**. The engines with 5,1KVA generators are also equipped with a protection system that causes the **engine to stop if the oil level is too low**.

The Genmac 5,1KVA Generator is equipped with **electronically controlled injection engines** of the GX series.





The 5,1KVA generator is equipped with capacitor voltage regulator, on request it can be supplied with AVR.

AVR Voltage Regulator

All models in the Genmac Combipro series are available with optional AVR voltage regulator. The AVR is a device that allows to **maintain the output more constant and less load-dependent**. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

The model equipped with AVR card is highly recommended, as it guarantees a significant improvement in the stability of the output voltage; this feature makes the generators particularly suitable with common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you can enjoy greater stability and thus increase the life of your devices.

TECHNICAL FEATURES OF GENERATOR GENMAC COMBIPRO RG5000HC-M5

Voltage regulator : capacitor (AVR Optional)

Power supply: Gasoline

Firing: Manual

Phase type: Single-phase

Continuous power: 4.4KVA / 4.0KW

Maximum power: 5.1KVA / 4.6KW

Motor: Honda GX270

Emission regulation: Stage V

Socket panel: 1 x schuko 230V - 1 x 16A 230V - 1 x 32A 230 V

Voltage: 230V

Frequency: 50 Hz

3000 rpm

Tank: 25 Lt.

Autonomy @ 75%: 15 h fixed rpm

Starting: Manual

Length (mm): 800

Width (mm): 640

Height (mm): 700

Dry weight (Kg): 89

If you are looking for another product then you can see on our catalog other

Images and technical data not binding.





Product features:

Phase: Single phase

Maximum power single phase (KW): 4.6

Continuous power single phase (KW): 4

Maximum power single phase (KVA): 4.4

Continuous power single phase (KVA): 5.1

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x schuko 230V - 1 x 16A 230V - 1 x 32A 230 V

Engine: Honda GX270

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Manual recoil

Cooling: Air

Poles: 2

Fuel tank capacity (L): 25

Running time (h): 15

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 800

Width (mm): 640

Height (mm): 700

Dry weight (Kg): 89

Silenced: Yes

Super silenced: No

ATS Switch device : No

Voltage regulator: AVR (optional)

Engine manufacturer: Honda