



# GENMAC Combiplus G11100KEO GENERATOR 12,3KVA

Product price:

**4,101.00 € tax excluded**

Product description:

## **GENMAC Combiplus G11100KEO THREE-PHASE GENERATOR 12,3KVA**

The generator Genmac Combiplus G11100KEO three phase is equipped with a Kohler diesel powered engine capable of delivering a power of 12,3KVA with capacitor voltage regulator (AVR optional).

Genmac Diesel professional high quality diesel generators, are equipped with a Kohler engine, which generates a continuous power of 11,0kva in only 3000 rpm and a maximum limited power (L.T.P.) of 12,3KVA . The engine is cooled by a fan, favoring and allowing a prolonged use of the generator without running the risk of overheating the mechanical parts that compose it.

Genmac professional diesel generators are highly reliable machines, built with quality components to be used in the professional field, where reliability is fundamental.

This feature is fundamental to ensure a high reliability of the generator, reduces its effort and increases its life span by lowering the noise level.

The 12,3KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

### **AVR Voltage Regulator**

All models in the Genmac Combipro series are available with optional AVR voltage regulator. The AVR is a device that allows to **maintain the output more constant and less load-dependent**. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

**The model equipped with AVR card is highly recommended**, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable



with common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you can enjoy greater stability and thus increase the life of your devices.

## TECHNICAL FEATURES OF GENERATOR GENMAC Combiplus G11100KEO 12,3KVA

Voltage regulator : capacitor (AVR Optional)

Power supply: Diesel

Firing: Electric

Phase type: Single phase / Three phase

Single phase continuous power: 3.6KVA / 3.3KW

Maximum single phase power: 4.1KVA / 3.7KW

Three-phase continuous power: 11.0KVA / 8.8KW

Three-phase maximum power: 12.3KVA / 9.8KW

Motor: Kohler KD425/2

Socket panel: 1 x 16A 230V - 1 x 16A 400V

Voltage: 230 / 400 V

Frequency: 50 Hz

3000 rpm

Tank: 19 Lt.

Autonomy @ 75%: 8 h fixed

Starting: Manual

Length (mm): 870

Width (mm): 620

Height (mm): 690

Dry weight (Kg): 173

If you are looking for another product then you can see on [our catalog other generator.](#)

Images and technical data are not binding.

### Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 3.7

Continuous power single phase (KW): 3.3

Maximum power single phase (KVA):

Continuous power single phase (KVA): 3.6

Maximum power three phase (KW): 9.8

Continuous power three phase (KW): 8.8

Maximum power three phase (KVA): 12.3

Continuous power three phase (KVA): 11



Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CE - 1 x 230V 16A 2P+T CE

Engine: Kohler KD 425/2

Engine rpm (rpm): 3000

Starting system: Electric

Cooling: Air

Poles: 2

Fuel tank capacity (L): 19

Running time (h): 8

Length (mm): 870

Width (mm): 620

Height (mm): 690

Dry weight (Kg): 173

ATS Switch device : Optional

Voltage regulator: AVR (optional)

Engine manufacturer: Kohler

