



# GENMAC Combiflash G221HO-M5 MOTOSALDATOR 7,2KVA

## Product description:

GENMAC Combiflash G221HO-M5 THREE-PHASE MOTOR WELDER 7,2KVA

Genmac Combiflash G221HO-M5 is a motorwelder is equipped with a Honda GX390 Stage V gasoline engine capable of delivering a power of 7,2KVA with capacitor voltage regulator (AVR optional).

The Genmac Combiflash G221HO-M5 is ideal for having electrical power always at hand in any place and environment (construction sites, markets, beaches, camping or for first aid in uncomfortable areas), combined with a powerful electrode welder.

The small size and moderate weight of the threephase 7,2KVA Genmac Combiflash G221HO-M5 motorwelder make it one of the most popular professional products in the Genmac line.

Equipped with a Honda GX390 engine capable of delivering a output of 7.2KVA with gasoline supply and an "air" cooling system by means of a fan, it guarantees maximum efficiency and durability even for long and continuous work as both a motorwelder and a welding machine. The motorwelder generates a maximum output of 7,2KVA in just 3000 rpm.

Start-up of the 7.2KVA Genmac Combiflash G221HO-M5 three-phase motorwelder is via an Manual start module.

## TECHNICAL CHARACTERISTICS OF GENMAC Combiflash G221HO-M5 7,2KVA

Power Supply: Gasoline

Starting: Manual

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Power: 2.4KVA / 1.9KW

Maximum ThreePhase Power: 7.2KVA / 5. 7KW





Welding Current: 40 - 200 A  
Maximum Welding Current: 220 A ac  
Service (A): 200 - 35% / 170 - 60%  
Welding Type: Electrode  
Voltage: 230 / 400 V  
Frequency: 50 Hz  
Motor: Honda GX 390  
Emission Standard: Stage V  
Socket panel: 1 x Schuko 16A 230V / 1 x 32A 400 V  
3000 rpm  
Tank: 19 Lt.  
Autonomy @ 75%: 9 h fixed rpm  
Length (mm): 810  
Width (mm): 550  
Height (mm): 680  
Dry weight (Kg): 99

If you are looking for another product then you can consult other motorwelder in our catalog.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 1.9  
Maximum power single phase (KVA): 2.4  
Maximum power three phase (KW): 5.7  
Maximum power three phase (KVA): 7.2  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: Honda GX390  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Pull starter  
Cooling: Air  
Poles: 2  
Welding current (A): 200 - 35% / 170 - 60%  
Type of welding: MMA  
Current max (A): 220  
Fuel tank capacity (L): 19  
Running time (h): 9  
Length (mm): 810





Width (mm): 550  
Height (mm): 680  
Dry weight (Kg): 99  
Silenced: Yes  
Super silenced: No  
Voltage regulator: No  
Engine manufacturer: Honda