



GENMAC Whisper RG10100KS-M5 GENERATOR 11,1KVA

Product description:

GENMAC WHISPER RG10100KS-M5 SINGLE-PHASE GENERATOR 11,1KVA

The Genmac Whisper RG10100KS-M5 single-phase generator features a gasoline-powered Kohler CH730 Stage V engine capable of delivering 11.1KVA with optional capacitor voltage regulator (AVR).

High quality professional silenced single phase gasoline power generator, Genmac with 11.1KVA power output. Genmac gasoline power generator is equipped with oversized Kohler air-cooled engine.

Genmac professional gasoline generators, are highly reliable machines, built with quality components to be used in the professional field, where reliability is paramount.

This feature is essential to ensure high reliability of the generator, reduces the strain on it and **increases its lifespan by lowering the noise level.**

All Kohler **motors** are built using the **best materials**, the **most innovative techniques** and the **most advanced methods of quality control.**

The 11.1KVA generator is equipped with a capacitor voltage regulator, upon request it can be supplied with AVR regulator.

Voltage Regulator AVR

All models in the Genmac series are available with an optional AVR voltage regulator. The AVR is a device that allows you to **keep the output more constant and less dependent on the load.** Thanks to this card there are fewer drops or spikes in current, making it safer to use the various devices connected, improving performance and durability.

The model equipped with AVR card is highly recommended, as it ensures a significant



improvement in the stability of the output; this feature makes the generators particularly suitable with commonly used machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

CARACTERISTICS OF GENERATOR GENMAC Whisper RG10100KS-M5 11.1KVA

Power supply: Gasoline

Continuous power PRP: 10KVA / 9KW

Standby power LTP: 11.1KVA / 10KW

Power factor $\cos \phi$: 0.9

Phase Type: Single Phase

VAC Voltage: 230 V

Frequency (Hz): 50

Voltage Regulator: Compound (AVR Optional)

ATS Panel: standard setup (Panel Optional)

Motor: Kohler CH730

Socket Panel: 1 x Schuko 16A 230V / 1 x 32A 230V / 1 x 63A 230V

Emissions Standard: STAGE 5

Tank capacity: 49 l

Range time at 75% of load: 25 h

RPM: 3000

Sound pressure: 65 dB(A) @ 7 m

Length (mm): 1100

Width (mm) 54

Height (mm) 924

Net weight (kg): 278

If you are looking for another product then you can consult on our catalog other [generators](#).

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 10

Continuous power single phase (KW): 9

Maximum power single phase (KVA): 11.1

Continuous power single phase (KVA): 10

Fuel: Gasoline



Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x Schuko 16A 230V / 1 x 32A 230V / 1 x 63A 230V

Engine: Kohler CH730

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Manual

Cooling: Air

Poles: 2

Tank capacity (L): 49

Running time (h): 25 at 75% of the load

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 1100

Width (mm): 540

Height (mm): 924

Dry weight (Kg): 278

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Kohler

