



GENMAC DAILY G7900HS-M5 GENERATOR 7,5KVA

Product price:

3,235.00 € tax excluded

Product description:

GENMAC DAILY G7900HS-M5 THREE-PHASE GENERATOR 7,5KVA

The **generator** Genmac Daily G7900HS-M5 three-phase is equipped with a gasoline powered **Honda** engine capable of delivering a power of **7,5KVA** with capacitor voltage regulator (AVR optional).

Genmac's high quality professional silenced three-phase gasoline generator with 7,5KVA power. The Genmac gasoline power generator is equipped with an oversized air-cooled Honda engine.

Genmac professional gasoline generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

This feature is fundamental to guarantee a high reliability of the generator, reduces its effort and increases its life span by lowering the noise level.

All Honda engines are built using the best materials, the most innovative techniques and the most advanced methods for quality control.

Each engine is thoroughly tested in order to prove its perfect functioning before delivery. In case of need, Honda's assistance service is always at your disposal.

The 7,5KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the **AVR regulator**.

AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving performance and durability.



The model equipped with AVR board is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily G7900HS-M5 7,5KVA

Power Supply: Gasoline

Single-phase PRP continuous power: 1.9KVA / 1.5KW Single-phase LTP standby power: 2.5KVA / 2KW Three-phase PRP continuous power: 5.6KVA / 4.5KW

Three-phase LTP standby power: 7. 5KVA / 6KW

Phase Type: Single Phase / Three Phase

VAC Voltage: 230 / 400 V

Frequency (Hz): 50

Voltage Regulator: Compound (AVR Optional) ATS Panel: standard setup (Panel Optional)

Motor: HONDA iGX390

Receptacle Panel: 1 x 16A 230V / 1 x 32A 230V / 1 x 16A 400V

Emissions Standard: STAGE 5

Tank capacity: 19 I

Autonomy at 75% load: 11 h

RPM: 3000

Sound pressure: 62 dB(A) @ 7 m

Length (mm): 1030 Width (mm) 620 Height (mm) 804 Net weight (kg): 192

If you are looking for another product then you can consult other terrestrial generators in <u>our catalog</u>.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase Maximum power single phase (KW): 2 Continuous power single phase (KW): 1.5 Maximum power single phase (KVA): 2.5 Continuous power single phase (KVA): 1.9 Maximum power three phase (KW): 6



Continuous power three phase (KW): 4.5 Maximum power three phase (KVA): 7.5 Continuous power three phase (KVA): 5.6

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 16A 230V / 1 x 32A 230V / 1 x 16A 400V

Engine: Honda iGX390

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Speed governor: Mechanical Starting system: Electric

Cooling: Air Poles: 2

Fuel tank capacity (L): 19 Running time (h): 11

Acoustic pressure: 62 dB(A) at 7 m

Length (mm): 1030 Width (mm): 620 Height (mm): 804 Dry weight (Kg): 192

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda

