

GENMAC Daily RG5000YS GENERATOR 6,1KVA



Product price:

3.065,00 € tax excluded

Product description:

GENMAC Daily RG5000YS SINGLE-PHASE GENERATOR 6,1KVA

The Genmac Daily RG5000YS single-phase generator is equipped with a Yanmar Diesel-powered engine capable of delivering a power of 6,1KVA with capacitor voltage regulator (AVR optional).

The Genmac Daily RG5000YS Diesel Generators, are highly reliable machines, built with quality components for use in the professional field, where reliability is paramount.

All **Yanmar engines** are built using the **best materials**, the **most innovative techniques** and the **most advanced quality control methods**.

This feature is critical to ensuring high reliability of the Genmac Daily RG5000YS generator, reducing strain and **increasing its lifespan by lowering noise levels**.

The 6.1KVA Genmac Daily RG5000YS is equipped with a capacitor voltage regulator, upon request it can be supplied with AVR.

Voltage Regulator AVR

All Genmac generators are available with optional AVR regulator. The AVR is a device that allows you to **keep the output more constant and less dependent on the load**. Thanks to this card there are fewer drops or spikes in current and this makes it safer to use the various devices connected, improving performance and durability.

The model equipped with AVR card is highly recommended, as it ensures a significant improvement in the stability of the output; this feature makes the generators particularly suitable with commonly used machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an



increase in the life of your devices.

TECHNICAL FEATURES GENERATOR GENMAC Daily RG5000YS 6.1KVA

Voltage Regulator : Capacitor (AVR Optional)

Power Supply: Diesel

Firing: Electric

Phase Type: Single Phase

Continuous Power: 5.0KVA / 4.5KW

Maximum Power: 6.1KVA / 5.5KW

Motor: Yanmar L100

Socket Frame: 1 x 16A 230V / 2 x 32A 230V

Voltage: 230V

Frequency: 50 Hz

3000 rpm

Sound pressure @7m : 68 dBa

Tank capacity: 19

Autonomy @ 75%: 15 h fixed rpm

Length (mm): 1030

Width (mm): 620

Height (mm): 804

Dry weight (Kg): 200

If you are looking for another product then you can consult on our catalog other terrestrial gensets.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 5.5

Continuous power single phase (KW): 4.5

Maximum power single phase (KVA): 6.1

Continuous power single phase (KVA): 5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 16A 230V / 2 x 32A 230V

Engine: Yanmar L100, 4 stroke

Engine rpm (rpm): 3000

Starting system: Electric

Cooling: Air



Poles: 2

Fuel tank capacity (L): 19

Running time (h): 15

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 1030

Width (mm): 620

Height (mm): 804

Dry weight (Kg): 200

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR (optional)

Engine manufacturer: Yanmar