



GENMAC DAILY G65000YS-M5 GENERATOR 6,9KVA

Product price:

3.334,00 € tax excluded

Product description:

GENMAC DAILY G65000YS-M5 THREE-PHASE GENERATOR 6,9KVA

The generator Genmac Daily G65000YS-M5 three phase is equipped with a Yanmar L100 Stage V motor powered by diesel capable of delivering a power of 6,9KVA with capacitor voltage regulator (AVR optional).

The Genmac Daily G65000YS-M diesel generator is equipped with an oversized air-cooled Yanmar motor. Genmac Daily G65000YS-M professional diesel generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

The Stage V engine allows the use of the generator set also for mobile use, for example for road construction sites and rental services. The generator is suitable for applications in different contexts such as: hospitals, industries, shopping centers, hotels, airports, banks, universities, stadiums, offices, etc..

All Yanmar engines are built using the best materials, the most innovative techniques and the most advanced quality control methods.

Each engine is thoroughly tested to prove that it works perfectly before delivery.

In case of need, Yanmar service is always at your disposal.

The Genmac Daily G65000YS-M generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

AVR Voltage Regulator

All Genmac series models are available with optional AVR regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load.



The model equipped with AVR board is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily G65000YS-M5 6,9KVA

Voltage regulator : capacitor (AVR Optional)

Power supply: Diesel

Starting: Electric

Phase type: Singlephase / Threephase

Singlephase continuous Output: 1.9KVA / 1.5KW

Maximum SinglePhase Output: 2.3KVA / 1.9KW

Continuous ThreePhase Output: 5.6KVA / 4.5KW

Maximum ThreePhase Output: 6.9KVA / 5.6KW

Motor: Yanmar L100

Emissions Standard: Stage V

Receptacle panel: 1 x 16A 230V - 1 x 32A 230V - 1 x 16A 400V

Voltage: 230 / 400 V

Frequency: 50 Hz

3000 rpm

Tank capacity: 19 l

Autonomy @ 75%: 15 h fixed revolutions

Sound pressure @7m: 67 dBa

Length (mm): 1030

Width (mm): 620

Height (mm): 804

Dry weight (Kg): 203

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 1.9

Continuous power single phase (KW): 1.5

Maximum power single phase (KVA): 2.3

Continuous power single phase (KVA): 1.9

Maximum power three phase (KW): 5.5





Continuous power three phase (KW): 4.5
Maximum power three phase (KVA): 6.9
Continuous power three phase (KVA): 5.6
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 16A 230V - 1 x 32A 230V - 1 x 16A 400V
Engine: Yanmar L100, 4 stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Cooling: Air
Poles: 2
Fuel tank capacity (L): 19
Running time (h): 15
Acoustic pressure: 67 dB(A) at 7 m
Length (mm): 1030
Width (mm): 620
Height (mm): 804
Dry weight (Kg): 203
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Yanmar