



GENMAC Urban-Rent RG9600KS-M5 GENERATOR 10,4KVA

Product price:

5,733.00 € tax excluded

Product description:

GENMAC Urban-Rent RG9600KS-M5 SINGLE-PHASE GENERATOR 10,4KVA

The generator GENMAC Urban-Rent RG9600KS-M5 single-phase is equipped with a diesel-powered Kohler engine capable of delivering 10,4KVA with AVR voltage regulator.

The high quality professional silenced diesel generator of the construction series, Genmac Urban-Rent with power of 10,4KVA, produced by Italian company Genmac. The generator is equipped with an oversized engine with water cooling and a practical electric starter.

For this line of generators is possible the supply of a differential protection circuit, in addition is possible the supply of trolleys for the handling of the unit.

The Genmac Urban-Rent silenced generator specific for mobile and rental applications. Easy to use and move. It mounts the latest generation engine with low emission level, for an energy that respects the environment.

Genmac 10,4KVA generators are highly reliable machines, built with quality components to be used in the professional field, where reliability is fundamental.

Genmac generators are supplied with AVR card, tank with collection tank and central lifting hook as standard on all models.

Control Panel

The control panel is composed as follows:

No. 1 CEE 63A 230V

No. 1 CEE 32A 230V

No. 2 CEE 16A 230V

No. 1 Schuko 16A 230V



Thermal circuit breaker

Circuit breaker

- Generator power monitoring (kW, kV Ar, kV A & pf)
- Fuel level meter
- Overload protection (kW & kV Ar)
- Low oil pressure protection
- High coolant temperature protection
- Low fuel level protection
- Charger alternator failure
- RPM protection
- Oil pressure and engine temperature readout

Analogue fuel level gauge Emergency stop button

Quick connector for remote start/ATS

On/off switch

AVR Voltage Regulator

The AVR is indispensable to make the generator work at its best, in fact it all needs an electronic control system, an AVR in fact, which ensures the proper functioning of the machine and the electrical network behind it.

The purpose of the AVR, in a current generator, is to keep the output stable. And if its operation is very simple when resistive loads are fed, more complex is the matter in case of mainly inductive loads: the delayed phase shift current counteracts the inductor magnetic field, causing a voltage drop at the alternator output terminals; to compensate for this phenomenon, the AVR intervenes automatically by increasing the excitation current, until the output returns to the nominal value. If the load is capacitive, the current acts as a magnetizer for the inductor causing an increase in the output voltage, and the AVR intervenes by reducing the excitation current.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Urban-Rent RG9600KS-M5 10,4KVA

Phase Type: Single Phase

Continuous Power: 9.4KVA / 8.5KW Maximum Power: 10.4KVA / 9.4KW

Engine: Kohler KDW702 Emissions Standard: Stage V

Starting: Electric Power Supply: Diesel

Receptacle Panel: 1 x Schuko 16A 230V - 2 x 16A 230V - 1 x 32A 230V - 1 x 63A 230V

Voltage: 230 V Frequency: 50 Hz Motor RPM: 3000 rpm Tank Capacity: 50 I



Autonomy @ 75%: 17 h fixed rpm

Voltage regulator: AVR

Sound pressure @7m: 67 dBa

Length (mm): 1475 Width (mm): 710 Height (mm): 1060 Dry weight (Kg): 400

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 9.4 Continuous power single phase (KW): 8.5 Maximum power single phase (KVA): 10.4 Continuous power single phase (KVA): 9.4

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x Schuko 16A 230V - 2 x 16A 230V - 1 x 32A 230V - 1 x 63A 230V

Engine: Kohler KDW702

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Electric

Cooling: Water

Poles: 2

Fuel tank capacity (L): 50 Running time (h): 17

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 1475 Width (mm): 710 Height (mm): 1060 Dry weight (Kg): 400

Silenced: Yes

Super silenced: Yes

ATS Switch device: Optional

Voltage regulator: AVR

Engine manufacturer: Kohler