



MASE MW 8/300 I-K MOTOSALDATOR 8KVA

Product price:

10,500.00 € tax excluded

Product description:

MASE MW 8/300 I-K MOTOSALDATOR 8KVA

The Motosaldator MASE MW 8/300 I-K threephase is equipped with a Kubota petrol-powered engine capable of delivering a power of 8KVA.

Mase motosaldator are generally used when it is not possible to use the power supply in arc welding: let's see today what are the parameters to evaluate and how to choose a motosaldator. Motosaldator, consisting of an electric generator and an electric welding machine, are often mounted on trolleys to be easily transported.

They are usually used for outdoor applications or in case it is problematic to supply through the mains, they can also be used indoors.

The 8KVA threephase Mase motosaldator is equipped with automatic stop for low oil level, it is complete with efficient and reliable safety systems with differential switch, protections for outputs.

The supply of the threephase motosaldator includes a handling kit equipped with two wheels and handles.

The threephase motosaldator Mase is asynchronous, self-excited and self-protected, capable of delivering a threephase power of 8KVA by means of a 19HP Kubota D722 engine. The feeding motor is electric starting and is water cooled, equipped with a tank with a capacity of 30 Lt that allows an autonomy with a load of 75% of 3.3 Lt/h approx.

Standard equipment

- Logic (DSE 3110) with digital display for the reading of the following parameters:
generator voltage, battery voltage, frequency, hour meter;
complete with automatic engine stop device with



alarm indication on the display in case of:

- failure to start
- low oil pressure
- high temperature water
- low fuel level
- over/low alternator voltage
- over/under alternator frequency
- Fuel level indicator
- Protections for power outputs
- 1 three-phase socket CEE 400V - 16A
- 1 single-phase socket CEE 230V - 32A
- Differential thermomagnetic circuit breaker
- Remote control socket
- Forced arc selector
- Automatic return to idle speed in the absence of
- Built-in 12V battery
- Central lifting hook

TECHNICAL CHARACTERISTICS OF MASE MW 8/300 I-K MOTOSALDATOR 8KVA

Maximum Singlephase output: 7 KVA

Maximum Threephase output: 8KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Engine: Kubota D722

Starting: Electric

Trigger voltage: 70 V

Maximum electrode diameter: 6 mm

Intermittency at 35%: 300A - 32V

Intermittency at 60%: 300A - 32V

Consumption: 3.3 Lt/h at 75% of load

Length: 1360 mm

Width: 530 mm

Height: 870 mm

Weight: 345 Kg

If you are looking for another product then you can consult other [Motosaldator](#) in our catalog.

Images and technical data are not binding.



Product features:

Phase: Single phase / Three phase

Maximum power single phase (KVA): 7

Maximum power three phase (KVA): 8

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: Kubota D722

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Ignition: Recoil

Starting system: Electric

Number cylinders: 1

Cooling: Water

Alternator: Gen Set asynchronous self-excited, self-protected

Open circuit voltage (V): 70

Maximum diameter electrodes (mm): 6

Fuel tank capacity (L): 30

Consumption (L/h): 3.3

Length (mm): 1360

Width (mm): 530

Height (mm): 870

Dry weight (Kg): 345

Inverter: No

AVR: No

Compound: No

Silenced: No

Super silenced: No