



IDROMAR MC2 DUPLEX WATERMAKER 260Lt/h

Product price:

18,400.00 € tax excluded

Product description:

IDROMAR MC2 DUPLEX WATERMAKER 260Lt/h

The Watermaker IDROMAR MC2 DUPLEX consists of two reverse osmosis plants in a single frame with simultaneous or independent operation with 260Lt/h flow rate.

IDROMAR MC2 DUPLEX is an osmosis plant recommended when the user's demand for drinking water is not satisfied by a single plant.

The IDROMAR Watermaker is a reverse osmosis system with flow rate 260Lt/h very compact and effective, thanks to its modular composition it is easy to install and operate.

The IDROMAR Watermaker with 260Lt/h flow rate is incredibly accessible to facilitate the ordinary or extraordinary maintenance operations and therefore all the majr works can be performed from the front panel.

It is also possible to design the unit with all built-in components such as the pre-feeding pump, sand filters and regeneration tank. The MC2 Duplex Watermaker clearly takes up more space but simplifies installation and the entire unit is compact and aesthetically pleasing.

The osmotic Watermaker units can work in either serated or simultaneous mode. The following data refers to 2 units operating simultaneously. Osmosis implantation has a number of matching accessories that improve reliability, efficiency and ease of operation and accessibility.

TECHNICAL CHARACTERISTICS HYDROMAR MC2 DUPLEX WATERMAKER 260Lt/h

Hourly production at 25°C: 260Lt/h Daily production at 25°C: 6200 Lt/day Salinity water produced: 300/400 PPM

Power consumption: 3 KW



Length: 800 mm Width: 490 mm Height: 800 mm Weight: 200 Kg

Hydraulic connections Sea suction: 1/2" x 2 Suction boxes: 1/2" x 2 Discharge: 3/8" x 2 Production: 3/8" x 2

If you are looking for another Watermaker similar to IDROMAR MC2 DUPLEX then we suggest you to browse our entire catalog dedicated to <u>nautical Watermaker</u>.

Images and technical data are not binding.

Product features:

Power (W): 1500 Length (mm): 800 Width (mm): 490 Height (mm): 800 Feed Type: 230 V

Production for hour at 25°C (Lt/h): 260 Daily production at 25°C (Lt/day): 6200 Salinity of water produced (PPM): 300/400

Capacity (Lt/h): 260 Remote panel: Digital Weight (Kg): 200

