



SEA RECOVERY AQUA MATIC 900-2 DESALINATOR 142 LT/H



Product description:

SEA RECOVERY AQUA MATIC 900-2 DESALINATOR 142LT/H

The desalinator SEA RECOVERY AQUA MATIC 900-2 is a reverse osmosis plant in compact or modular configuration with flow rate 142lt/h.

With just one touch, the Aqua Matic 900-2 will produce water, allowing boaters more time to relax and enjoy the cruise. The desalinator is equipped with an automatic pressure regulation and fresh water drainage system. The desalinator with a capacity of 142lt/h Sea Recovery the Aqua Matic 900-2 is able to perform self maintenance functions without the need for an operator. The automatic pressure regulation system automatically balances pressure levels according to any condition, allowing boaters to avoid the time-consuming work of manual pressure regulation.

The reverse osmosis with a flow rate of 142lt/h Aqua Matic 900-2 is compatible with NMEA 2000, giving boaters the ability to monitor and communicate with the reverse osmosis through any NMEA compatible display.

The NMEA 2000 protocol, also known by the abbreviations NMEA2k or N2K, allows to define a standard for serial, plug and play and bidirectional communication between marine devices that use the same protocol such as temperature sensors, wind direction and intensity detectors, but also motors, chart plotters, displays and so on.

The desalinator with 142lt/h Aqua Matic 900-2 is supplied with a color LCD touch screen that simplifies osmosis monitoring and operation, reminds and alerts the boat of any maintenance needs and if the performance or water quality falls below a certain level to ensure that the reverse osmosis system continues to operate optimally. The automatic rinsing system and LCD monitoring system optimize the performance of the trimmer and membrane because the osmosis system rinses every 7 days, whether the desalinator is producing water or in standby mode.

The desalinator with a capacity of 142lt/h Sea Recovery can be supplied in a compact or modular



configuration according to the customer's needs, allowing the use of the reverse osmosis even on boats or extremely narrow premises.

TECHNICAL CHARACTERISTICS DESALINATOR SEA RECOVERY AQUA MATIC 900-2
142lt/h

Vessel Number: 2

Water Production: 142lt/h

Daily Production: 3407lt/g

Performance: +-15% at 820 PSI / 57 BAR, 77°F / 25°C & 35,000 PPM TDS

Filter Type: Sea Strainer with a cleanable Monel Mesh Screen filter, Charcoal Filter Assembly, Commercial Prefilter, and Oil Water Separator

Pressure Adjustment Control Type: Automatic

Salinity Range: Designed for seawater use up to 50,000 PPM TDS

Length: 710 mm

Width: 457 mm

Height: 421 mm

Weight: 75 kg

If you are looking for another desalinator similar to Sea Recovery then we suggest you to browse our entire catalog dedicated to [nautical desalinators](#).

Images and technical data are not binding.

Product features:

Length (mm): 710

Width (mm): 457

Height (mm): 421

Dry weight (Kg): 75

Production for hour at 25°C (Lt/h): 142

Daily production at 25°C (Lt/day): 3407

