



SEA RECOVERY AQUA MATIC 1400-2 DESALINATOR 221 LT/H



Product description:

SEA RECOVERY AQUA MATIC 1400-2 DESALINATOR 221LT/H

The desalinator SEA RECOVERY AQUA MATIC 1400-2 is a reverse osmosis plant in compact or modular configuration with flow rate 221lt/h.

With just one touch, the Aqua Matic 1400-2 will produce water, allowing boaters more time to relax and enjoy the cruise. The desalinator is equipped with an automatic pressure regulation and fresh water drainage system. The desalinator with a capacity of 221lt/h Sea Recovery the Aqua Matic 900-1 is able to perform self maintenance functions without the need for an operator. The automatic pressure regulation system automatically balances pressure levels according to any condition, allowing boaters to avoid the time-consuming work of manual pressure regulation.

The reverse osmosis with a flow rate of 221lt/h Aqua Matic 1400-2 is compatible with NMEA 2000, giving boaters the ability to monitor and communicate with the reverse osmosis through any NMEA compatible display.

Functions and controls are available everywhere in the NMEA 2000 network, and can be quickly configured with a single touch of the menu. The navigators can also start and stop the osmosis from the remote display. The easy-to-use touch screen displays explanatory images of all operating conditions.

The desalinator with 221lt/h Aqua Matic 1400-2 is supplied with a color LCD touch screen that simplifies osmosis monitoring and operation, reminds and alerts the boat of any maintenance needs and if the performance or water quality falls below a certain level to ensure that the reverse osmosis system continues to operate optimally. The automatic rinsing system and LCD monitoring system optimize the performance of the trimmer and membrane because the osmosis system rinses every 7 days, whether the desalinator is producing water or in standby mode.

The desalinator with a capacity of 221lt/h Sea Recovery can be supplied in a compact or modular



configuration according to the customer's needs, allowing the use of the reverse osmosis even on boats or extremely narrow premises.

TECHNICAL CHARACTERISTICS DESALINATOR SEA RECOVERY AQUA MATIC 1400-2
221lt/h

Vessel Number: 2

Water Production: 221lt/h

Daily Production: 5300lt/g

Performance: +-15% at 820 PSI / 57 BAR, 77°F / 25°C & 35,000 PPM TDS

Filter Type: Sea Strainer with a cleanable Monel Mesh Screen filter, Charcoal Filter Assembly, Commercial Prefilter, and Oil Water Separator

Pressure Adjustment Control Type: Automatic

Salinity Range: Designed for seawater use up to 50,000 PPM TDS

Length: 964 mm

Width: 457 mm

Height: 421 mm

Weight: 76 kg

If you are looking for another desalinator similar to Sea Recovery then we suggest you to browse our entire catalog dedicated to [nautical desalinators](#).

Images and technical data are not binding.

Product features:

Length (mm): 964

Width (mm): 457

Height (mm): 421

Dry weight (Kg): 76

Production for hour at 25°C (Lt/h): 221

Daily production at 25°C (Lt/day): 5300

