



MECC ALTE ECP28-VL/4 C-TYPE THREE-PHASE ALTERNATOR 30KVA

Product description:

MECC ALTE ECP28-VL/4 C-TYPE ALTERNATOR 30KVA THREEPHASE DSR

Alternator MECC ALTE ECP28-VL/4 C-TYPE with a power of 30KVA, this unit has a Brushless self-exciting and self-regulating operation equipped with voltage regulator **DSR**.

The ECP28-VL/4 C-TYPE alternator is designed to operate at 50 or 60 HZ frequency, the possibility of working on these two frequencies makes it possible to apply it for any service voltage increasing its versatility, for the correct operation. For correct operation it is only necessary to verify that the calibrations are correct for the intended use.

MECC ALTE ECP28-VL/4 is supplied with 12 terminals (7 terminals), with which it is normally possible to connect the alternator both in series star and parallel star. According to the needs it is possible to pass from a connection to another one keeping in mind that it is necessary to verify the DSR.

ECP28-VL/4 C-TYPE can be used as single-phase depending on the needs. MECC ALTE ECP28-VL/4 is equipped with digital current regulator DSR. The regulator is suitable for operation on both three-phase and single-phase generators, allowing fast, accurate and reliable set-up.

All MECC ALTE ECP28 alternators have the MAUX auxiliary winding to power the DSR digital regulator. You can connect the DSR voltage regulator to your PC via the DxR2 USB interface and DxR TERMINAL software to query/download alarms and settings for analysis. The DSR has a built-in USB and can be connected to the PC without any optional connection card. Other settings such as LAMS, external synchronous digital RAM-based control and soft start are achievable through the DxR connection.

The mechanical design used the most advanced FEM techniques. The materials used are FEP12 steel for the frame, C45 steel for the shaft and cast iron or pressure die-cast aluminum for the end supports. The fans are made of die-cast



aluminum or fiberglass filled nylon, UL compliant materials. The rotors are dynamically balanced according to ISO 1940-1 grades 6.3 (up to Series 32) or 2.5 (Series 34 and up).

Select the alternator that reflects the **technical specifications you require**, visit our [dedicated section](#) to find out how.

TECHNICAL FEATURES OF 30KVA MECC ALTE ALTERNATOR ECP28-VL/4 C-TYPE

Phase Type: Single Phase / Three Phase
Maximum Three Phase Power: 33KVA / 26.4KW
Three Phase Continuous Power: 30KVA / 24KW
Maximum Single Phase Power: 22.3KVA / 22.3KW
Single Phase Continuous Power: 20.5KVA / 20.5KW
Frequency: 50 / 60 Hz
Voltage: 230 V / 400 V
Protection class: IP23
Alternator speed: 1500 / 1800 rpm
Number of poles: 4
Efficiency: 87.9%
Weight: 141.8 Kg
Width: 466.7 mm
Length: 593 mm
Height: 460 mm
Constant speed alternator
Brushless
Voltage regulator: AVR

Looking for a product with different features? [HERE](#) you can find the full range MECC ALTE and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 22.3
Continuous power single phase (KW):
Maximum power single phase (KVA): 22.3
Continuous power single phase (KVA): 20.5
Maximum power three phase (KW): 26.4
Continuous power three phase (KW): 24
Maximum power three phase (KVA): 33
Continuous power three phase (KVA): 30



Frequency (Hz): 50 / 60
Voltage (V): 230 / 400
Engine rpm (rpm): 1500 / 1800
Poles: 4
Single-phase power (KVA): 22.3
Three-phase power (KVA): 33
Efficiency (%): 87.9
Protection degree: IP23
Acoustic pressure: 57 dB(A) at 7 m
Brushes: No
PMG: No
Type of alternator: Constant Speed
Voltage regulator: AVR
Weight (Kg): 161