



Shop name



MOSA GE 20 YSXC STAGE V

Product price:

8,968.00 € tax excluded

Product description:

MOSA GE20 YSXC 16 KW generating set

MOSA GE20 YSXC threephase 16 KW generator set with Yanmar 4TNV88 diesel engine. The MOSA GE20 YSXC generator set is equipped with electric start and, thanks to the engine, it is also suitable for mobile use. The alternator of the MOSA GE20 YSXC is synchronous, three-phase, self-excited, self-regulated, brushless with class H insulation with compound+AVR voltage regulator.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, 610 kg weight as well as its practical drilled base.

The MOSA GE20 YSXC generator set with 60-liter tank has a fuel consumption of 3.4 liters/hour at 75% load for an autonomy of more than 17 hours.

Sockets:

1x 400V 63A 3P+T CEE

1x 400V 32A 3P+T CEE

1x 400V 16A 3P+T CEE

2x 230V 16A 2P+T CEE

Technical specifications:

Three-phase Stand-By Power (LTP) 20 kVA (16 kW) / 400V / 28.9 A

Three-phase power PRP 18 kVA (14.4 kW) / 400V / 26 A

Single-phase power PRP 7 kVA / 230V / 30.4 A

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Fuel capacity: 60 l

Engine: Yanmar 4TNV88



Starter: Electric

Measured sound power LwA: 93 dB(A) (68 dB(A) @ 7m)

Guaranteed sound power LwA (LpA pressure) 94 dB(A) (69 dB(A) @ 7m)

Consumption: 3.4 Lt/h at 75% load

Length: 1720 mm

Width: 1000 mm

Height: 1130 mm

Weight: 610 Kg

Supersilenced

AVR + COMPOUND

Emissions regulations: Stage V

MOSA GE20 YSXC generator set - Yanmar diesel engine electric start - Three-phase alternator - Three-phase power 18 kVA (14.4 kW)

If you are looking for another product such as the generator set MOSA GE20 YSXC then you can see on our catalog other [terrestrial generators](#).

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Continuous power single phase (KVA): 7

Maximum power three phase (KW): 16

Continuous power three phase (KW): 14.4

Maximum power three phase (KVA): 20

Continuous power three phase (KVA): 18

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: Yanmar 4TNV88, 4 stroke naturally aspirated

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm³): 2190

Number cylinders: 4

Cooling: Water

Inyección : Direct

Alternator: Three-phase synchronous self-excited, self-regulated, brushless

Length (mm): 1720



Shop name

Width (mm): 1000

Height (mm): 1130

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR+Compound

Engine manufacturer: Yanmar



PrestaShop