



MOSA GE 20 YSXC



Product price:

8.968,00 € tax excluded

Product description:

MOSA GE20 YSXC 16 KW generating set

MOSA GE20 YSXC threephase 16 KW generator set with Yanmar 4TNV88 diesel engine. The MOSA GE20 YSXC generator set is equipped with electric start and, thanks to the engine, it is also suitable for mobile use. The alternator of the MOSA GE20 YSXC is synchronous, three-phase, self-excited, self-regulated, brushless with class H insulation with compound+AVR voltage regulator.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, 610 kg weight as well as its practical drilled base.

The MOSA GE20 YSXC generator set with 60-liter tank has a fuel consumption of 3.4 liters/hour at 75% load for an autonomy of more than 17 hours.

Sockets:

1x 400V 63A 3P+T CEE
1x 400V 32A 3P+T CEE
1x 400V 16A 3P+T CEE
2x 230V 16A 2P+T CEE

Technical specifications:

Three-phase Stand-By Power (LTP) 20 kVA (16 kW) / 400V / 28.9 A

Three-phase power PRP 18 kVA (14.4 kW) / 400V / 26 A

Single-phase power PRP 7 kVA / 230V / 30.4 A

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Fuel capacity: 60 l





Engine: Yanmar 4TNV88
Starter: Electric
Measured sound power LwA: 93 dB(A) (68 dB(A) @ 7m)
Guaranteed sound power LwA (LpA pressure) 94 dB(A) (69 dB(A) @ 7m)
Consumption: 3.4 Lt/h at 75% load
Length: 1720 mm
Width: 1000 mm
Height: 1130 mm
Weight: 610 Kg
Supersilenced
AVR + COMPOUND
Emissions regulations: Stage V

MOSA GE20 YSXC generator set - Yanmar diesel engine electric start - Three-phase alternator -
Three-phase power 18 kVA (14.4 kW)

If you are looking for another product such as the generator set MOSA GE20 YSXC then you can see on our catalog other terrestrial generators.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Continuous power single phase (KVA): 7
Maximum power three phase (KW): 16
Continuous power three phase (KW): 14.4
Maximum power three phase (KVA): 20
Continuous power three phase (KVA): 18
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Yanmar 4TNV88, 4 stroke naturally aspirated
Emissions Regulations: Stage 5
Engine rpm (rpm): 1500
Starting system: Electric
Engine capacity (cm³): 2190
Number cylinders: 4
Cooling: Water
Inyección : Direct
Alternator: Three-phase synchronous self-excited, self-regulated, brushless



Length (mm): 1720

Width (mm): 1000

Height (mm): 1130

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR+Compound

Engine manufacturer: Yanmar