



HONDA Outboard BF150AK2 XCU WHITE Long Shaft 110.3kW

Product description:

HONDA OUTBOARD BF150AK2 XCU WHITE LONG LEG

Honda BF150AK2 XCU WHITE are outboard engines perfect for professional use, they are reliable, compact and lightweight complete with PGM-Fi electronic fuel injection system.

Honda BF150AK2 XCU are optimized to offer more power for a wide range of different boats. The decisive, smooth power this advanced technology offers is sure to put a smile on your face as you venture out on the water.

VTEC™ is an efficient system included in the Honda BF150AK2 XCU WHITE outboard that keeps fuel consumption down while delivering an exciting increase in power. In the Honda BF150AK2 XCU it works by using two different cams:

- 1) When the outboard is running at low rpm, the valves are operated by a cam less aggressively ensuring low fuel consumption and excellent performance.
- 2) As the outboard speed increases to 5000 rpm, the VTEC™ hydraulically operates a cam with a higher lift profile. This keeps the valves open longer, getting more air into the combustion chamber to produce optimum power, just like in a Formula One race car.

The Honda BF150AK2 XCU WHITE outboard features BLAST™ ready-to-start technology that gets the engine up to velocity in seconds. The BLAST™ (Boosted Low Speed Torque) delivers high torque even at low speeds by unleashing powerful thrust from startup. The ECU automatically advances the ignition timing, and at the same time increases the fuel/air ratio to give you more thrust from low speeds.

Honda BF150AK2 XCU is equipped with ECOMo's special poor-blend combustion control system ensures remarkable fuel economy right from revs and performance. The Honda BF150AK2 XCU models are NMEA2000® compliant.

HONDA BF150AK2 XCU WHITE TECHNICAL FEATURES



Net Power (kW): 110.3
Net Power (Hp): 150
Displacement: 2354 cm³
Shaft Length: Extra Long
Dry weight (Kg): 217
Starter: Electric
Ignition system: Electronic PGM-IG
Type of control Remote
Setup and engine lifting: Electric
Transom height (mm): 508
Length (mm): 845
Width (mm): 580
Height (mm): 1665
Bore x stroke: 87 x 99 mm
Engine Brand: Honda
Engine Type: DOHC, 4 stroke
Number of cylinders: 4
Speed at full throttle (rpm): 5000-6000
Cooling system: Water
Battery charging capacity (A): 40
Exhaust system: Propeller hub
Propeller rotation: Counter-rotating

Are you looking for an outboard with different technical specifications? [Here](#) you can find the full range of Honda or other specialized brands.

The images are purely indicative.

Product features:

Fuel: Gasoline
Engine: DOHC, 4 tempi
Ignition: Electronic PGM-IG
Starting system: Electric
Engine capacity (cm³): 2354
Number cylinders: 4
Cylinders' position: In line
Cooling: Water (with thermostat)
Bore x stroke (mm): 87 x 99
Reduction ratio: 2.14
Rpm at full throttle (rpm): 5000 - 6000
Appearance and engine lifting: Electric
Transom height (mm): 508



Shop name

Net power (kW): 110.3

Length (mm): 845

Width (mm): 580

Height (mm): 1665

Dry weight (Kg): 217

Shaft Length: L

Controls: Remote



PrestaShop