



CGM PR4-160LSP

Product description:

CGM PR4-160LSP LED Light Tower with CGM petrol engine

The CGM PR4-160LSP is a simple light tower with manual lifting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

CGM PR4-160LSP consists of a trolley with lockable handles with safety grip.

CGM PR4-160LSP includes CGM 6000SP SUPER POWER gasoline engine with electric start, 3000 rpm and air cooling.

CGM PR4-160LSP is equipped with a galvanized steel lifting tower capable of extending to a maximum height of 5.5 meters, including 3 feet of stabilization to secure the light tower once opened.

CGM PR4-160LSP TECHNICAL SPECIFICATIONS

Lights: 4 160W LEDs Lit Area: 2200 Sq Ft Max Height: 5. 5 Mt

Lift: Manual

Telescopic Pole: galvanized steel Wind stability: nr 3 stabilizers Lumen per light: 20350 lm

Electrical power: 6 KVA / 5,4 KW

Rotation: 355 degrees

Trolley: Slow

Drives for forklift: nr 2 Power socket: 16A 230V

Voltage: 230V





Frequency: 50 Hz

Number of turns: 3000 turns/mn

Engine: 6000SP SUPER POWER CGM

Fueling: Gasoline

Type of starting: Electric Tank capacity: 25 Lt

Autonomy with working lights: 20 hr

Engine power: 14 Hp

N. Cylinders: 1
Intake: Aspirated

Cooling: Air

Width: 1300 mm Length: 900 mm

Height Closed: 2160 mm Height Open: 5500 mm Dry Weight: 280 Kg

Firing: Air

AVR

You can find many other different light towers in the section dedicated to lighting systems.

Images are purely indicative

Product features:

Phase: Single phase

Continuous power single phase (KW): 5.4 Continuous power single phase (KVA): 6

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 230V 16A Engine: 6000SP SUPER POWER CGM

Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 420

Number cylinders: 1

Cooling: Air Alternator: CGM

Poles: 2

Type of lamps: LED





Lamps: 4 x 160 W

Telescopic pole: Galvanized steel

Illuminated area (m²): 2200 Total lumens (Lm): 81400

Lifting System: Manual lifting system

Maximum height (m): 5.5

Mast rotation: 355°

Open size (mm): 1300 x 900 x 5500 Closed size (mm): 1300 x 900 x 2160

Transportability: Slow Trailer Fuel tank capacity (L): 25 Running time (h): 20

Acoustic pressure: 70 dB(A) at 7 m

Dry weight (Kg): 280

Silenced: Yes

Engine manufacturer: CGM