



CGM PR4-160LCX

Product price:

3,695.00 € tax excluded

Product description:

CGM PR4-160LCX LED with Honda Petrol Engine

The CGM PR4-160LCX is a simple light tower with manual lifting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

CGM light tower consists of a trolley with lockable handles with safety grip.

CGM PR4-160LCX includes a HONDA GSX270 gasoline engine with electric start, 3000 rpm and air cooling.

CGM PR4-160LCX is equipped with a galvanized steel lifting tower capable of extending to a maximum height of 5.5 meters, including 3 feet of stabilization to secure the light tower once opened.

TECHNICAL SPECIFICATIONS CGM PR4-160LCX



Floodlights: 4 LED 160W Illuminated Area: 2200 Mq

Max Height: 5.5 Mt

Lift: Manual

Telescopic pole: galvanized steel Wind Stability: nr 3 stabilizers Lumen per luminaire: 20350 lm Electrical power: 5 KVA / 4.5 KW

Rotation: 355 degrees Towing trolley: Lento Forklift guides: nr 2 Power outlet: 16A 230V

Voltage: 230V Frequency: 50 Hz

Number of revolutions: 3000 revolutions/mn

Engine: HONDA GSX270

Feeding: Gasoline Starting type: Electric Tank capacity: 15 Lt

Autonomy with working lights: 20 hr Engine power: 7.8 Hp / 5.8 KW

N. Cylinders: 1 Suction: Aspirated

Cooling: Air Width: 1300 mm Length: 900 mm

Height Closed: 2160 mm Height Opened: 5500 mm

Dry weight: 280 Kg

Cooling: Air

AVR

You can find many other different light towers in the section dedicated to lighting systems.

Images are purely indicative

Product features:

Phase: Single phase

Continuous power single phase (KW): 4.5 Continuous power single phase (KVA): 5

Fuel: Gasoline



Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 230V 16A

Engine: HONDA GSX270 Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 270

Number cylinders: 1

Cooling: Air

Alternator: NSM/LINZ ELECTRIC

Poles: 2

Type of lamps: LED Lamps: 4 x 160 W

Telescopic pole: Galvanized steel

Illuminated area (m²): 2200 Total lumens (Lm): 81400

Lifting System: Manual lifting system

Maximum height (m): 5.5

Mast rotation: 355°

Open size (mm): 1300 x 900 x 5500 Closed size (mm): 1300 x 900 x 2160

Transportability: Slow Trailer Fuel tank capacity (L): 25 Running time (h): 20

Acoustic pressure: 70 dB(A) at 7 m

Dry weight (Kg): 280

Silenced: Yes

Engine manufacturer: Honda

