



# CGM FXS4-320L TOWERGEN

Product price:

**8,756.00 € tax excluded**



## Product description:

### CGM FXS4-320L TOWERGEN 4 X 320W

CGM FXS4-320L TOWERGEN is a light tower with diesel generator and manual lifting winch equipped with 4 floodlights able to deliver a light power of 320W each.

CGM FXS4-320L TOWERGEN is equipped with a KOHLER KD350 3000 rpm diesel engine with liquid cooling capable of delivering a mechanical power of 5.8 Hp.

CGM FXS4-320L TOWERGEN is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 7.5 meters, including 4 stabilization feet to secure the light tower once opened.

CGM FXS4-320L is equipped with LINZ ELECTRIC alternator which increases the efficiency of the KOHLER engine thanks to its integrated AVR, allowing high efficiency with reduced consumption. The light tower has a 40 Lt capacity tank, which allows the continuous operation of the CGM for 84 hours.

## TECHNICAL FEATURES CGM FXS4-320L TOWERGEN

Floodlights: 4 LED 350W

Illuminated Area: 4500 Mq

Max Height: 7.5 Mt

Lift: Manual

Telescopic Pole: Galvanized steel with self-braking winch from 450

Wind stability: nr 4 stabilizers

Guides for forklift forks: n.4



Lumen per light: 41550 lm  
Continuous electric power: 4.2 KVA  
Rotation: 355 degrees  
Towing trolley: Slow  
Power outlet: 16A 230V  
Voltage: 230V  
Frequency: 50Hz  
Number of revolutions: 3000 revolutions/mn  
Engine: KOHLER KD350 Diesel  
Starting type: Electric battery  
Tank capacity: 40 Lt  
Autonomy with working lights: 84 hr  
Engine power: 5.8 Hp / 4.3 KW  
N. Cylinders: 1  
Suction: Aspirated  
Cooling: Air  
Alternator: LINZ ELECTRIC  
Type: Brushless  
No. of Poles: 2  
Width: 1200 mm  
Length Closed: 1550 mm  
Length Opened: 2400 mm  
Height Closed: 2700 mm  
Height Opened: 7500 mm  
Dry weight: 625 Kg  
Voltage regulation: AVR

Looking for a light tower with different features? [Here](#) you can find the full range CGM or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

**Product features:**

Phase: Single phase  
Continuous power single phase (KVA): 4.2  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 2 x 230V 16A CE  
Engine: KOHLER KD350  
Engine rpm (rpm): 3000  
Starting system: Elettrico

---



---

Number cylinders: 1  
Cooling: Air  
Alternator: Linz  
Poles: 2  
Maximum height (m): 7.5  
Tank capacity (L): 40  
Type of lamps: LED  
Lamps: 4 x 320 W  
Telescopic pole: Galvanized steel  
Illuminated area (m<sup>2</sup>): 4500  
Lifting System: Manual lifting system  
Mast rotation: 355°  
Open size (mm): 2400 x 1200 x 7500  
Closed size (mm): 1550 x 1200 x 2700  
Dry weight (Kg):  
AVR: Yes