



CGM AD4-320L

Product price:

14,079.00 € tax excluded

Product description:

CGM AD4-320L 4 X 320W LIGHTER TOWER

CGM AD4-320L is a light tower with diesel generator and manual lifting winch equipped with 4 floodlights capable of delivering a light output of 320W each.

CGM AD4-320L is equipped with KOHLER KDW702 diesel engine, 1500 rpm with liquid cooling capable of delivering a mechanical power of 6.6 Hp.

CGM AD4-320L is equipped with a galvanized steel lifting tower capable of extending to a maximum height of 8.5 meters, including 4 feet of stabilization to secure the light tower once opened.

CGM AD4-320L is equipped with LINZ ELECTRIC alternator that increases the effectiveness of the KOHLER engine due to its integrated AVR, allowing high efficiency with low consumption. The fairy tower has a 120Lt capacity tank, which allows the continuous operation of the CGM for 240 hours.

TECHNICAL FEATURES CGM AD4-320L

Floodlights: 4 LED 320W Illuminated Area: 5000 Mq

Max Height: 8.5 Mt

Lift: Hydraulic

Telescopic Pole: Galvanized steel with self-braking winch from 450

Wind Stability: nr 4 stabilizers Guides for forklift forks: n.4 Lumen per light: 41550 lm

Continuous electric power: 3.5 KVA

Rotation: 359 degrees



Towing trolley: Slow Power outlet: 16A 230V

Voltage: 230V Frequency: 50Hz

Number of revolutions: 1500 revolutions/mn

Engine: KOHLER KDW702 Starting type: Battery electric

Tank capacity: 120 Lt

Autonomy with working lights: 240 hr Engine power: 6.6 Hp / 4.9 KW

N. Cylinders: 2 in Line Suction: Aspirated Cooling: Water

Alternator: LINZ ELECTRIC

Type: Brushless No. of Poles: 4 Width: 2330 mm Length: 1470 mm

Height Closed: 2450 mm Height Opened: 8500 mm

Dry weight: 850 Kg Voltage regulation: AVR

Looking for a light tower with different features? <u>Here</u> you can find the full range CGM or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Phase: Single phase

Continuous power single phase (KVA): 3.5

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 230V 16A

Engine: KOHLER KDW702 Engine rpm (rpm): 1500 Starting system: Electric Number cylinders: 2

Cylinders' position: In line

Cooling: Water Alternator: Linz



Poles: 4

Tank capacity (L): Type of lamps: LED Lamps: 4 x 320 W

Telescopic pole: Galvanized steel

Illuminated area (m²): 5000

Lifting System: Hydraulic lifting system

Maximum height (m): 8.5

Mast rotation: 359°

Open size (mm): 2330 x 1470 x 8500 Closed size (mm): 2330 x 1470 x 2450

Dry weight (Kg): 850

AVR: Yes

