



CGM OK 4-320L

Product description:

CGM OK4-320L 4 X 320W

CGM OK4-320L is a light tower with diesel generator, hydraulic lifting equipped with 4 floodlights capable of delivering a light output of 320W each.

CGM OK4-320L is equipped with KOHLER KDW702 diesel engine, 1500 rpm with liquid cooling capable of delivering a mechanical power of 6.6 Hp.

CGM OK4-320L is equipped with a galvanized steel lifting tower capable of extending up to 8.5 meters in maximum height, including 4 stabilization feet to secure the light tower once opened. The lifting tower is electrically operated and by a hydraulic system that allows maximum extension without effort.

CGM OK4-320L is equipped with LINZ ELECTRIC alternator which increases the effectiveness of the KOHLER engine thanks to its integrated voltage regulator, allowing high efficiency with low consumption. The fact tower has a 140Lt capacity tank, which allows the continuous operation of the CGM for 280 hours.

CGM OK4-320L TECHNICAL FEATURES

Floodlights: 4 LED 320W

Illuminated Area: 5000 Mq

Max Height: 8.5 Mt

Lift: Hydraulic motorized

Telescopic pole: Galvanized steel

Wind Stability: nr 4 stabilizers

Guides for forklift forks: n.8

Lumen per luminaire: 41550 lm

Continuous electric power: 3.5 KVA



Rotation: 359 degrees
Power outlet: 230V (max 1,8kVA)
Voltage: 230V
Frequency: 50Hz
Number of turns: 1500 turns/mn
Engine: KOHLER KDW702
Starting type: Electric battery
Tank capacity: 140 Lt
Autonomy with working lights: 280 hr
Engine power: 6.6 Hp / 4.9 KW
N. Cylinders: 2 in line
Suction: Aspirated
Cooling: Water
Alternator: LINZ ELECTRIC
Type: Brushless
No. of Poles: 4
Width: 1200 mm
Length: 1130 mm
Height Closed: 2450 mm
Height Opened: 8500 mm
Dry weight: 810 Kg
Voltage regulation: Condenser

Looking for a light tower with different features? Here you can find the full range CGM or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Phase: Single phase
Continuous power single phase (KVA): 3.5
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V
Engine: KOHLER KDW702
Engine rpm (rpm): 1500
Starting system: Electric
Number cylinders: 2
Cylinders' position: In line
Cooling: Water
Alternator: Linz





Poles: 4

Tank capacity (L): 140

Type of lamps: LED

Lamps: 4 x 320W

Telescopic pole: Galvanized steel

Illuminated area (m²): 5000

Lifting System: Hydraulic lifting system

Maximum height (m): 8.5

Mast rotation: 359°

Open size (mm): 1200 x 1130 x 8500

Closed size (mm): 1200 x 1130 x 2450

Dry weight (Kg): 810

