



CGM BE4-160L BE TOWER



Product description:

CGM BE TOWER BE4-160L LIGHTER TOWER 160W X 4

CGM BE4-160L is a galvanized steel telescopic light tower equipped with 4 LED projectors each capable of delivering a light output of 160W.

The BE TOWER CGM BE4-160L light tower has an input plug and a 16A 230V output socket for the with which it can be combined with other units.

CGM BE4-160L is designed to be combined with a CGM generator set and can be connected in series in order to use one generator for multiple lighting units.

CGM BE4-160L TECHNICAL SPECIFICATIONS

Floodlights: 4 x 160W Ioduri

Illuminated Area: 3000 @ 5 lux

Max Height: 8.5 Mt

Lift: Hydraulic

Telescopic pole: Telescopic pole in galvanized steel

Wind Stability: nr 4 stabilizers

Lumen per luminaire: 20350 lm

Total lumens: 81400 lm

Rotation: 359 degrees

Forklift guides: nr 8

Power outlet: 16A 3P input plug

Connectable in series: YES

Voltage: 230V



Frequency: 50 Hz

Width: 1200 mm

Length: 1000 mm

Height Opened: 8500 mm

Height Closed: 2300 mm

Dry weight: 550 Kg

Looking for a Light Tower with different characteristics? [Here](#) you can find the whole range of CGM or other specialized brands

Images and technical data are not binding and may be subject to change by the supplier

Product features:

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A 3P CEE

Type of lamps: LED

Lamps: 4 x 160 W

Telescopic pole: Galvanized steel

Illuminated area (m²): 3000

Total lumens (Lm): 81400

Lifting System: Hydraulic lifting system

Maximum height (m): 8.5

Mast rotation: 359°

Open size (mm): 1200 x 1000 x 8500

Closed size (mm): 1200 x 1000 x 2300

Dry weight (Kg): 550

