



# CGM BE4-160L BE TOWER

## Product description:

CGM BE TOWER BE4-160L LIGHTER TOWER 160W X 4

CGM BE4-160L is a galvanized steel telescopic light tower equipped with 4 LED projectors each capable of delivering a light output of 160W.

The BE TOWER CGM BE4-160L light tower has an input plug and a 16A 230V output socket for the with which it can be combined with other units.

CGM BE4-160L is designed to be combined with a CGM generator set and can be connected in series in order to use one generator for multiple lighting units.

## CGM BE4-160L TECHNICAL SPECIFICATIONS

Floodlights: 4 x 160W Ioduri

Illuminated Area: 3000 @ 5 lux

Max Height: 8.5 Mt

Lift: Hydraulic

Telescopic pole: Telescopic pole in galvanized steel

Wind Stability: nr 4 stabilizers

Lumen per luminaire: 20350 lm

Total lumens: 81400 lm

Rotation: 359 degrees

Forklift guides: nr 8

Power outlet: 16A 3P input plug

Connectable in series: YES

Voltage: 230V

Frequency: 50 Hz

Width: 1200 mm

Length: 1000 mm

Height Opened: 8500 mm





Height Closed: 2300 mm

Dry weight: 550 Kg

Looking for a Light Tower with different characteristics? Here you can find the whole range of CGM or other specialized brands

Images and technical data are not binding and may be subject to change by the supplier

**Product features:**

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A 3P CEE

Type of lamps: LED

Lamps: 4 x 160 W

Telescopic pole: Galvanized steel

Illuminated area (m<sup>2</sup>): 3000

Total lumens (Lm): 81400

Lifting System: Hydraulic lifting system

Maximum height (m): 8.5

Mast rotation: 359°

Open size (mm): 1200 x 1000 x 8500

Closed size (mm): 1200 x 1000 x 2300

Dry weight (Kg): 550

