



MECC ALTE ECP32-1S/2 C-TYPE THREE PHASE ALTERNATOR 44 KVA AVR

Product price:

2,520.19 € tax excluded

Product description:

MECC ALTE ECP32-1S/2 C-TYPE THREEPHASE ALTERNATOR 44 KVA DSR

Alternator MECC ALTE ECP32-1S/2 C-TYPE with an output of 44KVA, this unit has a self-exciting and self-regulating Brushless operation equipped with **DSR** voltage regulator.

The alternator ECP32-1S/2 is complete with self-regulation which is achieved by means of a digital electronic regulator powered by an auxiliary winding.

The MECC ALTE ECP32-1S/2 alternator is ruggedly designed to meet industry requirements and the most demanding technological specifications needed in various applications. They are available as a bearing in single or double bearing configuration. To couple them to a main engine, you can choose from a wide range of flanges and fittings.

The MECC ALTE ECP32-1S/2 alternator consists of a fixed stator with slotted slots and a rotating inductor. In addition, models above 15 KVA are equipped with a damping cage as standard. All alternator windings have a 2/3 pitch in order to reduce harmonic content.

MECC ALTE ECP32-1S/2 alternators comply with Italian standard CEI 2-3 file 11111. This standard corresponds to the European EN 60034-1 and the international IEC 60034-1, is linked to the British BS 4999 Part 101, is equivalent to the German VDE 0530 Part 1 and is included in the French NF 51.111.

TECHNICAL FEATURES MECC ALTE ALTERNATOR ECP32-1S/2 C-TYPE

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Output:

(50Hz) 29 KVA / 29 KW



(60Hz) 35 KVA / 35 KW

Singl Phase Continuous Output:

(50Hz) 26.4 KVA / 26.4 KW

(60Hz) 31.7 KVA / 31.7 KW

Maximum thre-phase output:

(50Hz) 44 KVA / 35.2 KW

(60Hz) 53 KVA / 42.4 KW

ThreePhase Continuous Output:

(50Hz) 40 KVA / 32 KW

(60Hz) 48 KVA / 38.4 KW

Frequency: 50 / 60 Hz Voltage: 230 / 400 V

Degree of Protection: IP23

Alternator revolutions: 3000 rpm

Number of Poles: 2 Efficiency: 87.4% Width: 542.7 mm Length: 613.5 mm Height: 542.7 mm Weight: 173 Kg

Constant speed alternator

Brushless

Voltage regulator: AVR

Looking for a product with different features? <u>Here</u> you can find the full range MECC ALTE and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 29 (50Hz) - 35 (60Hz)

Continuous power single phase (KW): 26.4 (50Hz) - 31.7 (60Hz)

Maximum power single phase (KVA): 29 (50Hz) - 35 (60Hz)

Continuous power single phase (KVA): 26.4 (50Hz) - 31.7 (60Hz)

Maximum power three phase (KW): 35.2 (50Hz) - 42.4 (60Hz)

Continuous power three phase (KW): 32 (50Hz) - 38.4 (60Hz)

Maximum power three phase (KVA): 44 (50Hz) - 53 (60Hz)

Continuous power three phase (KVA): 40 (50Hz) - 48 (60Hz)

Frequency (Hz): 50 / 60 Voltage (V): 230 / 400

Engine rpm (rpm): 3000



Poles: 2

Single-phase power (KVA): 35 Three-phase power (KVA): 53

Efficiency (%): 88.9 Protection degree: IP23

Acoustic pressure: 77 dB(A) at 7 m

Length (mm): 658 Width (mm): 392 Height (mm): 606 Dry weight (Kg): 173

Brushes: No PMG: No

Type of alternator: Constant Speed

Voltage regulator: AVR

Weight (Kg): 225

