



MECC ALTE ECP32-M/2 C-TYPE THREE PHASE ALTERNATOR 66 KVA AVR

Product description:

MECC ALTE ECP32-M/2 C-TYPE THREEPHASE ALTERNATOR 66 KVA DSR

Alternator MECC ALTE ECP32-M/2 C-TYPE threephase with a power of 66KVA, this unit has a Brushless self-exciting and self-regulating operation equipped with **DSR** voltage regulator.

The ECP32-M/2 alternator is complete with self-regulation which is achieved through a digital electronic regulator powered by an auxiliary winding.

The MECC ALTE ECP32-M/2 alternator is ruggedly suited to meet industry requirements and the most demanding technological specifications needed in various applications. They are available as a bearing in single or dual bearing configurations.

The ECP32-M/2 alternator consists of a fixed stator with inclined slots and a rotating inductor. In addition, models above 15 KVA are equipped with a damping cage as standard.

The Standard level of protection refers to a generator that has the only impregnation resin applied to all active parts. Note that this level is standard on the Mecc Alte ECP32-M/2 series of generators: the voltages from turn to turn in this series are never dangerous for the duration of the insulation, so it is not necessary to apply any additional protection paint.

The ECP32-M/2 alternators comply with the Italian CEI 2-3 file 11111. This corresponds to the European EN 60034-1 and the international IEC 60034-1, is linked to the British BS 4999 Part 101, is equivalent to the German standard VDE 0530 Part 1 and is included in the French NF 51.111.

TECHNICAL CHARACTERISTICS MECC HIGH ALTERNATOR ECP32-M/2 C-TYPE

Phase Type: SinglePhase / ThreePhase





Maximum SinglPhase Output:
(50Hz) 43KVA / 43KW
(60Hz) 51.5KVA / 51.5KW
Singlephase continuous output:
(50Hz) 39KVA / 39KW
(60Hz) 46.8KVA / 46.8KW
Threephase maximum output:
(50Hz) 66KVA / 52.8KW
(60Hz) 79.5KVA / 63.6KW
Threephase continuous output:
(50Hz) 60KVA / 48KW
(60Hz) 72KVA / 57.6KW
Frequency: 50 / 60Hz
Voltage: 230 / 400 V
Degree of Protection: IP23
Alternator RPM: 3000 rpm
Number of Poles: 2
Efficiency: 88.4%
Width: 553 mm
Length: 683.5 mm
Height: 542.7 mm
Weight: 212 Kg
Constant speed alternator
Brushless
Voltage regulator: AVR

Looking for a product with different features? Here you can find the full range MECC ALTE and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 43 (50Hz) - 51.5 (60Hz)
Continuous power single phase (KW): 39 (50Hz) - 46.8 (60Hz)
Maximum power single phase (KVA): 43 (50Hz) - 51.5 (60Hz)
Continuous power single phase (KVA): 39 (50Hz) - 46.8 (60Hz)
Maximum power three phase (KW): 52.8 (50Hz) - 63.6 (60Hz)
Continuous power three phase (KW): 48 (50Hz) - 57.6 (60Hz)
Maximum power three phase (KVA): 66 (50Hz) - 79.5 (60Hz)
Continuous power three phase (KVA): 60 (50Hz) - 72 (60Hz)
Frequency (Hz): 50 / 60





Voltage (V): 230 / 400
Engine rpm (rpm): 3000
Poles: 2
Single-phase power (KVA): 51.5
Three-phase power (KVA): 79.5
Efficiency (%): 88.4
Protection degree: IP23
Acoustic pressure: 77 dB(A) at 7 m
Length (mm): 553
Width (mm): 683.5
Height (mm): 542.7
Dry weight (Kg): 212
Brushes: No
PMG: No
Type of alternator: Constant Speed
Voltage regulator: AVR
Weight (Kg): 225

