



LARIUS GIOTTO K12480 AIRLESS PUMP

Product price:

1.922,00 € tax excluded

Product description:

LARIUS GIOTTO k12480 AIRLESS PUMP

Pump LARIUS GIOTTO K12480 electric diaphragm, apparatus used for high-pressure spraying without the aid of air. The pump is driven by an electric motor coupled to an eccentric shaft.

The shaft acts on the hydraulic piston which, by pumping oil from the hydraulic case, sends the suction membrane into fibrillation. The movement of the membrane creates a depression. The product is sucked in, pushed towards the outlet of the pump and sent through the hose to the guns. A hydraulic valve placed at the head of the hydraulic case allows to regulate and control the pressure of the material exiting the pump.

LARIUS GIOTTO K12480 allows the spraying of liquids under high pressure, covering large surfaces with sanitizing agents, thus reducing the presence of bacteria, fungi and viruses. Through the use of the LARIUS GIOTTO pump, atomization is more effective, allowing the treatment of a larger surface area with less fluid consumption than other low-pressure systems.

The LARIUS GIOTTO K12480 pump is equipped with a trolley complete with handle that allows a comfortable and easy transport.

The LARIUS GIOTTO pump is equipped with a practical regulator that allows to set in a precise way the delivery of the jet.

TECHNICAL FEATURES LARIUS GIOTTO K12480 PUMP

Max flow rate: 8 l/m

Motor power: 2.2 Kw

Max pressure: 220 bar

Power supply: 110 /220/380 VAC

Frequency: 50 Hz



Sound pressure level: ? 75dB (A)

Guns: 1 AT 250 gun

Nozzle size: Up to 0.033"

Minimum motor-generator power: 5.5 Kw

Length: 1000 mm

Width: 600 mm

Height: 850 mm

Weight: 56 Kg

Are you looking for an electric pump with different features? HERE you can find the whole range LARIUS or other specialized brands

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service accepts no liability for any changes made by the manufacturer.

Product features:

Frequency (Hz): 50

Voltage (V): 115 / 230

Maximum output capacity (Lt/min): 8

Pressure (bars): 220 Max

Length (mm): 1000

Width (mm): 600

Height (mm): 850

Dry weight (Kg): 56

Nozzle's largest diameter: 0.033"

Version: Trolley

Type of pumping group: Membrane

