



# AURORA LIGHT TOWER ALPHA K2-L 6X160 - S WITH SLOW TOWING TROLLEY

## Product description:

### **AURORA LIGHTHOUSE TOWER ALPHA K2-L 6X160 - S WITH TOWING CART**

AURORA ALPHA K2-L 6X160 - S is a light tower with generator equipped with Kohler 15LD350 Diesel engine and manual hoisting winch equipped with 6 floodlights capable of delivering a light output of 160W each.

AURORA ALPHA K2-L 6X160 - S is equipped with a galvanized steel lifting tower able to extend up to 8,5 meters of maximum height, including 4 stabilization feet to secure the light tower once opened. The lifting system is operated manually and by a hydraulic system that allows the maximum extension without effort.

AURORA ALPHA K2-L 6X160 - S is equipped with Kohler 15LD350, super efficient 3000 rpm engine. AURORA ALPHA K2-L 6X160 - S light towers in addition guarantee you an autonomy of 180 h of work at 30% of the load.

AURORA ALPHA K2-L 6X160 - S light towers.

The AURORA light tower lenses feature extremely special optics designed specifically for the civil engineering and construction sectors. This innovative fully directional LED lens design ensures maximization of light spread and reduction of waste.

A single AURORA ALPHA tower can cover an area of 4200 m<sup>2</sup>, ensuring a brighter, safer and more productive site.

AURORA ALPHA K2-L 6X160 - S comes complete with a slow moving trolley, giving the customer the ability to easily transport the light tower.

**TECHNICAL CHARACTERISTICS AURORA ALPHA K2-L 6X160 - S**



---

Manufacturer: Green Power  
Projectors: 6 160W LEDs  
Lighted Area: 4200 Sq Ft  
Max Height: 8.5 Mt  
Lift: Manual  
Motor: Kohler 15LD350  
Emissions: Stage V  
Power supply: Diesel  
Engine speed: 3000 rpm  
Telescopic pole: Galvanized steel  
Wind resistance max: 100 Km/h  
Wind stability: nr 4 stabilizers  
Transport: Slow towing  
Noise level at 7 mt: 70 dB (A)  
Total lumens: 122100 lm  
Voltage: 230V  
Frequency: 50 Hz  
Autonomy 30% load: 180 hr  
Closed dimensions: 1154x1118x2430 mm  
Open dimensions: 2030x2202x8500 mm  
Dry weight: 560 Kg

Looking for a product with different characteristics? [Here](#) you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to manufacturer's revisions.

#### **Product features:**

Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Engine rpm (rpm): 3000  
Starting system: Electric  
Type of lamps: LED  
Lamps: 6 x 160W

---



Telescopic pole: Galvanized steel

Illuminated area (m<sup>2</sup>): 4200

Total lumens (Lm): 122100

Lifting System: Hydraulic lifting system

Maximum height (m): 8.5

Mast rotation: 350°

Open size (mm): 2030x2202x8500

Closed size (mm): 1154x1118x2430

Transportability: Slow Trailer

Dry weight (Kg): 560

Engine manufacturer:

