



## AURORA LIGHT TOWER ALPHA K2-L 4X320 - F WITH FAST TOWING TROLLEY

**Product price:** 

9,220.00 € tax excluded

## **Product description:**

## AURORA LIGHT TOWER ALPHA K2-L 4X320 - F WITH FAST TOWING TROLLEY

AURORA ALPHA K2-L 4X320 - F is a light tower with generator equipped with Kohler 15LD350 Diesel engine and manual hoisting winch equipped with 4 floodlights capable of delivering a light output of 320W each.

AURORA ALPHA K2-L 4X320 - F is equipped with a galvanized steel lifting tower able to extend up to 8,5 meters of maximum height, including 4 stabilization feet to secure the light tower once opened. The lifting system is operated manually and by a hydraulic system that allows maximum extension without effort.

AURORA ALPHA K2-L 4X320 - F comes with Kohler 15LD350 engine, this engine is super efficient with 3000 rpm. The AURORA ALPHA in addition guarantee you an autonomy of 180 h of work at 30% of the load.

The AURORA light tower lenses feature extremely special optics designed specifically for the civil engineering and construction sectors. This innovative fully directional LED lens design ensures maximization of light spread and reduction of waste.

A single AURORA ALPHA tower can cover an area of 5000 m2, ensuring a brighter, safer and more productive site. AURORA ALPHA K2-L 4X320 - F is supplied complete with fast towing trolley complete with autonomous braking system, complete with rear lights with integrated reverse light and all the features for proper urban and extra-urban transport.

TECHNICAL CHARACTERISTICS AURORA ALPHA K2-L 4X320 - F

Manufacturer: Green Power



Projectors: 4 320W LEDs

Lighted Area: 5000 Square Meter

Max Height: 8.5 Mt

Lift: Manual

Engine: Kohler 15LD350 Emissions: Stage V Power supply: Diesel Engine speed: 3000 rpm

Telescopic pole: Galvanized steel Wind resistance max: 100 Km/h Wind stability: nr 4 stabilizers Transport: Fast towing trolley Noise level at 7 mt: 70 dB (A) Total lumens: 166200 lm

Voltage: 230V Frequency: 50 Hz

Autonomy 30% load: 180 hr

Closed dimensions: 1154x1118x2430 mm Open dimensions: 2030x2202x8500 mm

Dry weight: 560 Kg

Looking for a product with different characteristics? <u>Here</u> you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revision.

## **Product features:**

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Electric Type of lamps: LED

Lamps: 4 x 320W



Telescopic pole: Galvanized steel

Illuminated area (m²): 5000 Total lumens (Lm): 166200

Lifting System: Hydraulic lifting system

Maximum height (m): 8.5

Mast rotation: 350°

Open size (mm): 2030x2202x8500 mm Closed size (mm): 1154x1118x2430 mm

With generator / Without generator: With generator

Transportability: Fast Trailer

Stability to wind (Km/h): 100 Km/h

Dry weight (Kg): 560

Engine manufacturer: Kohler 15LD350

