



HONDA FF 300 POWER TILLER 57 cc

Product price:

1,827.00 € tax excluded

Product description:

HONDA FF300 POWER TILLER 57cc

HONDA FF300 is a counter-rotating power tiller complete with a 4-stroke Honda GXV57 engine capable of delivering a net output of 1.5KW.

HONDA FF300 is a powerful and reliable power tiller suitable for any kind of application. They are very easy to handle and their special counter-rotating tiller speeds up work enormously.

Using the HONDA FF300 is as easy as taking a walk. That's because the high-performance 4-stroke engine has multiple gears and delivers just the amount of power you need each time, regardless of the working conditions.

HONDA FF300 delivers stable and reliable power with reduced and cleaner emissions, plus 4-stroke gasoline engines avoid the mess associated with mixing oil and fuel.

HONDA FF300 do not require a warm-up interval to achieve maximum performance. This results in excellent fuel economy and, as a result, greater savings.

HONDA thanks to its powerful 4-themes, the transmission unit and a strong clutch, the HONDA FF300 rotary tiller is able to unleash all its power towards the counter-rotating blades, allowing you to have an excellent result with minimum effort and use of time.

TECHNICAL CHARACTERISTICS POWER TILLER:

Maximum working width: 410 mm

Maximum working depth: 160 mm

Forward speed: 3

Reverse speed: 1

Forward rotation speed (rpm): 0.15 - 1 m/s



Reverse rotation speed (rpm): 0.3 m/s
PTO rotation speed (low/high) (rpm): 131
Dimensions (W x D x H): 1,465 x 465 x 1,010 mm
Dry weight (kg): 50.5
Engine: OHC 4 Stroke
model: GXV57
Engine displacement (cc): 57
net output(kW/rpm): 1.5/4.800
Fuel tank capacity (liters): 1
Engine oil capacity (liters). 0.26
Starting: Reel start
Transmission clutch: Manual - Expansion spindle
Transmission: Wheels - Epicyclic bevel gear
Final Drive: Wheels - Constant gear - Chain and gear cutters
Differential / side clutch: Yes
Sound pressure at operator's ear (dB(A)+): 74
Guaranteed sound output level (dB(A)++): 92
Vibration (m/sec²): 4.5

If you are looking for a HONDA POWER TILLER with other features then you can see our entire catalog of [motor hoes](#).

Product features:

Fuel: Gasoline
Engine: Honda GXV57 4 tempi
Engine rpm (rpm): 4800
Ignition: Recoil
Starting system: Pull starter with recoil
Engine capacity (cm³): 57
Oil capacity (L): 0.26
Working width (mm): 410
Transmission: Constant Gear
Net power (kW): 1.5
Fuel tank capacity (L): 1
Acoustic power: 92 dB(A)
Acoustic pressure: 74 dB(A)
Length (mm): 1465
Width (mm): 465
Height (mm): 1010
Dry weight (Kg): 50.5



Shop name

Speeds:

Max tilling depth (mm) : 160

Engine manufacturer: Honda



PrestaShop