



# AURORA TOWER LIGHT TAU L 4X160

**Product price:**

**5.068,34 € tax excluded**

## **Product description:**

### AURORA TAU L4X160 TOWER LIGHTER

AURORA TAU L4X160 is a light tower with manual lifting equipped with 4 floodlights capable of providing a light output of 160W each.

AURORA TAU L4X160 is equipped with a galvanized steel lifting tower able to extend up to 9.5 meters of maximum height. The tower is complete with a hand pump for raising and manual locking on each extension to avoid the rotation of the same and to ensure the maximum extension of the column even in the absence of air inside.

AURORA TAU L4X160 stands out for its performance, compactness and solidity, with its 4X160W halogen lights, able to compete with much bulkier lighting towers equipped with a halogen system.

The lighting tower AURORA is not equipped with an integrated generator, it is the ideal product for those who already have a source of energy or connection to the electrical network.

AURORA TAU L4X160 is suitable for a variety of large-scale construction work, maintenance repair, accident management and disaster relief work, high-brightness lighting needs.

The AURORA TAU L4X160 light tower has an input plug and a 16A 230V output socket for the with which it can be combined with other units.

AURORA TAU L4X160 is designed to be combined with a generator set and can be connected in series in order to use one generator for multiple lighting units.

AURORA TAU L4X1600 is characterized by extremely compact dimensions and squared shape that optimize and facilitate its positioning and transportation on mobile means.

## TECHNICAL FEATURES AURORA TAU L4X160



Manufacturer: Green Power  
Projectors: 4 x 160W LED  
Lit area: 3500 square meters  
Total lumens: 81400 lm  
Max height: 9.5 Mt  
Lifting: Manual  
Pole sections: 4  
Rotation: 355°  
Max wind resistance: 110 Km/h  
Transportation: Stationary  
Manual stabilizers: 4  
Lifting hooks: 2  
Fork passage guides: STD  
Extra sockets: 1 x 16A CEE / 230 V  
Voltage: 230V  
Frequency: 50 Hz  
Contained tower dimensions: 1180x980x2523 mm  
Open tower dimensions: 2710x2514x9500 mm  
Dry weight: 550 Kg

Looking for a product with different characteristics? Here you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

#### **Product features:**

Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x 16A CEE / 230 V  
Type of lamps: LED  
Lamps: 4 x 160W  
Telescopic pole: Galvanized steel  
Illuminated area (m²): 3500  
Total lumens (Lm): 81400  
Lifting System: Manual lifting system  
Maximum height (m): 9.5  
Mast rotation: 355°  
Open size (mm): 2710x2514x9500  
Closed size (mm): 1180x980x2523  
With generator / Without generator: Without generator  
Transportability: Stationary  
Dry weight (Kg): 550



