



AURORA TOWER LIGHT OMEGA 75-L 4X160 - SF

Product price:

4,537.10 € tax excluded

Product description:

AURORA OMEGA 75-L4X160 - SF LIGHTER TOWER

AURORA OMEGA 75-L4X160 - SF is a tower light with manual lifting equipped with 4 floodlights capable of delivering a light output of 320W each.

AURORA OMEGA 75-L4X160 - SF is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 7.5 meters. The tower is complete with a hand pump for lifting and manual locking on each extension to avoid the rotation of the same and to ensure the maximum extension of the column even in the absence of air inside.

AURORA OMEGA 75-L4X160 - SF stands out for its performance, compactness and solidity, with its 4X160W halogen lights, able to compete with much bulkier lighting towers equipped with a halogen system.

The AURORA OMEGA 75-L4X160 - SF lighting tower has an input plug and a 16A 230V output socket for the with which it can be combined with other units. AURORA OMEGA 75-L4X160 - SF are mobile lighting units designed to ensure maximum reliability of operation even in the harshest environments.

One of the most characteristic elements is the upper protection of the telescopic pole, an AURORA exclusive, which safeguards one of the most delicate points of the entire AURORA OMEGA 75-L4X160 - SF from atmospheric agents, building site slag, dust and leaves.

The Aurora light tower is equipped with a fast towing trolley complete with autonomous braking system, complete with rear lights with integrated reverse light and all the features for a proper urban and extra-urban transport.

TECHNICAL FEATURES AURORA OMEGA 75-L4X160 - SF



Manufacturer: Green Power Projectors: 4 Led 160W

Lit Area: 3000 Square meters

Total Lumen: 81400 lm Max Height: 7. 5 Mt

Rise: Manual Pole sections: 4 Rotation: 350°

Max wind resistance: 110 Km/h

Transport: slow towing Manual stabilizers: 4 + 1

Lifting hooks: 4

Fork passage guides: STD

Useful dimensions of generating set: 720 x 1600 mm

Extra sockets: 1 x 16A CEE / 230 V

Voltage: 230V Frequency: 50 Hz

Contained tower dimensions: 2125x1202x2335 mm Open tower dimensions: 3004x1800x7500 mm

Dry weight: 340 Kg

Looking for a product with different characteristics? <u>Here</u> you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 16A CEE / 230 V

Type of lamps: LED Lamps: 4 x 160W

Telescopic pole: Galvanized steel

Illuminated area (m²): 3000 Total lumens (Lm): 81400

Lifting System: Manual lifting system

Maximum height (m): 7.5

Mast rotation: 350°

Open size (mm): 3500x1705x7100 Closed size (mm): 500x1705x2450



With generator / Without generator: Without generator Transportability: Slow Trailer Dry weight (Kg): 340

