



AURORA TOWER LIGHT OMEGA 85-L 4X320 - FF

Product price:

9.418,76 € tax excluded

Product description:

AURORA OMEGA 85-L4X320 - FF LIGHTING TOWER

AURORA OMEGA 85-L4X320 - FF is a tower light with hydraulic lifting equipped with 4 floodlights capable of providing a light output of 320W each.

AURORA OMEGA 85-L4X320 - FF is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 8.5 meters. The tower is complete with automatic hydraulic lift.

AURORA OMEGA 85-L4X320 - FF stands out for its performance, compactness and solidity, with its 4X320W halogen lights, able to compete with much bulkier lighting towers equipped with a halogen system.

The AURORA OMEGA 85-L4X320 - FF light tower has an input plug and a 16A 230V output socket for the with which it can be combined with other units. AURORA OMEGA 85-L4X320 - FF are mobile lighting units designed to ensure maximum reliability of operation even in the harshest environments.

AURORA OMEGA 85-L4X320 - FF is equipped with a fast towing trolley complete with autonomous braking system, complete with rear lights with integrated reverse light and all the functions for a correct urban and extra-urban transport.

AURORA OMEGA 85-L4X320 - FF are mobile lighting units designed to ensure maximum reliability of operation even in the harshest environments.

One of the most distinguishing elements is the upper protection of the telescopic pole, an AURORA exclusive, which safeguards one of the most delicate points of the entire AURORA OMEGA 85-L4X320 - FF from atmospheric agents, building site waste, dust and leaves.

TECHNICAL CHARACTERISTICS AURORA OMEGA 85-L4X320 - FF





Manufacturer: Green Power Projectors: 4 Led 320W

Lit Area: 5000 Square meters Total Lumen: 166200 lm

Max Height: 8.5 Mt Lift: Hydraulic Pole sections: 4

Rotation: 350°

Max wind resistance: 110 Km/h Transportation: fast towing Manual stabilizers: 4 + 1

Lifting hooks: 4

Fork passage guides: STD

Useful dimensions generator set: 960 x 1800 mm

Extra sockets: 1 x 16A CEE / 230 V

Voltage: 230V Frequency: 50 Hz

Contained tower dimensions: 3500x1705x2600 mm Open tower dimensions: 3500x1705x8500 mm

Dry weight: 400 Kg

Are you looking for a product with different characteristics? Here you can find the full range Green Power or other specialized brands.

The images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 16A CEE / 230 V

Type of lamps: LED Lamps: 4 x 320W

Telescopic pole: Galvanized steel

Illuminated area (m2): 5000 Total lumens (Lm): 166200

Lifting System: Hydraulic lifting system

Maximum height (m): 8.5

Mast rotation: 350°

Open size (mm): 3500x1705x8500 Closed size (mm): 3500x1705x2600

With generator / Without generator: Without generator

Transportability: Fast Trailer





Dry weight (Kg): 400

