



# ULTIMATE80-20W UNDERWATER LED SPOTLIGHT

**Product price:**

**488,00 € tax excluded**

## **Product description:**

### ULTIMATE80-20W UNDERWATER LED LIGHT

ULTIMATE80-20W is an underwater LED boat spotlight capable of generating 1400 lumens of light output with On/Off remote control switch.

The ULTIMATE80-20W's internal heat sink can be easily removed for maintenance and upgrades without the hassle of running your boat dry.

With 1400 lumens of spotlight output and a 60-degree beam angle, the ULTIMATE 80-20 led is recommended for fiberglass and wood hull boats up to 20 feet. We recommend that the light be installed at least 250mm below the waterline when the yacht is loaded.

ULTIMATE80-20W is recommended for boats over 30m, installing each fixture 1-3m apart for the best illumination. This flush mount underwater spotlight uses a ULTIMATE80-20W screw-in body for installation in GRP, fiberglass and wood hulls. The Led light is serviced from inside the hull.

The ULTIMATE80-20W underwater light features the smallest and brightest welded Led projectors on the market with wire inserts for angular hull adjustment.

The ULTIMATE80-20W underwater spotlight can be supplied in your choice of colors: S02860W with white, S02860B with Royal blue, S02860G with Green and 02860R with Red.

ULTIMATE80-20W comes complete with Lloyd's certification on all components.

### ULTIMATE80-20W TECHNICAL SPECIFICATIONS

Hull Material: GRP / fiberglass / Wooden

Boat Size: Up to 20 m

Spacing: 1 m up to 3 m





Beam Angle: 60 °

Installation Angles: Flush

Lumen: 1400

Kelvin: 7200

Typical LED life expectancy: 30000 h

Minimum and Maximum Operating Voltage: 12-24V AC

Current / Amplifier: 1.6 - 0.8 amp

Driver Type: Integral

Output Drivers: N/A

Control Options: Switch On & Off

Device Length: 117 mm

Device Diameter: 80 mm

Profile (height) of fixture. 5 mm

Required removal space: 160 mm

Total Weight: 1 kg

Cable length: Custom

Cut out hole: 61 mm

Material: Aluminum / Nickel coated / Bronze

Growth resistant lens: Borosilicate glass

Max Hull thickness: 65 mm

Looking for an Underwater spotlight with different features? Here you can find the section dedicated to nautical lighting systems with brands specializing in the field.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

#### **Product features:**

Voltage (V): 12-24 DC

Diameter (Ø): 80 mm

Average life of LEDs (hrs): 30000

Type of lamps: LED

Total lumens (Lm): 1400

Length (mm): 117

Weight (Kg): 1

Video: mSzY-vFJivE

