



MECC ALTE ES16W-75 SINGLE PHASE ALTERNATOR 2.3 KVA

Product description:

MECC ALTE ES16W-75 SINGLEPHASE ALTERNATOR 2.3 KVA

The alternator singlephase MECC ALTE ES16W-75 with 2 poles is able to deliver a continuous power of 2,3KVA complete with ASR voltage regulator.

The MECC ALTE ES16W-75 alternators are designed to be exceptionally versatile, they are made to be suitable for all applications where an easy-to-transport power source is needed.

Mecc Alte portable alternators are available with a wide range of shafts, flanges and fittings. The 2-pole rotors have a damping cage and the stator windings have a reduced pitch to reduce harmonic content.

The alternator MECC ALTE ES16W-75 single-phase alternators are designed without brushes and offer high operational reliability. As there are no collectors or sliding contacts, minimal maintenance is required. The three phase range is designed with brushes and slip ring and is controlled by the transformer. This allows for high load capacity, ideal for motor starting applications.

The alternator MECC ALTE ES16W-75 range is single phase AVR controlled, but designed with brushes and slip ring to allow good voltage regulation and better motor starting; power loads other than power factor 1.0, such as modern electronic products or pumps.

MECC HIGH TECHNICAL CHARACTERISTICS ES16W-75

Phase type: Single phase

Singlephase maximum output: 2 KW

Singlephase continuous output: 1.6 KW

Singlephase maximum output: 2.5 KVA

Singlephase continuous output: 2.3 KVA



Frequency: 50 - 60 Hz
Voltage: 230 V
Degree of protection: IP21
Alternator speed: 3000 rpm
Number of poles: 2
Sound pressure level: 72 dBA (56 dBA at 7 m)
Efficiency: 73.7%.
Weight: 15,6 Kg
Constant speed alternator
Voltage regulator: ASR

Are you looking for an alternator with different characteristics? Here you can find all MECC ALTE range and other specialized brands

Images and technical data are not binding and may be subject to manufacturer's revisions.

Product features:

Phase: Single phase
Maximum power single phase (KW): 2
Continuous power single phase (KW): 1.6
Maximum power single phase (KVA): 2.5
Continuous power single phase (KVA): 2.3
Frequency (Hz): 50 / 60
Voltage (V): 230
Engine rpm (rpm): 3000
Poles: 2
Single-phase power (KVA): 2.7
Efficiency (%): 73.7
Protection degree: IP21
Acoustic power: 72 dB(A)
Acoustic pressure: 56 dB(A) at 7 m
Brushes: Yes
PMG: No
Type of alternator: Constant Speed
Voltage regulator: ASR
Weight (Kg): 14.3

