



ELC LUMAPHORE LED 600XL

Product price:

1.917,00 € tax excluded

Product description:

LUMAPHORE LED 600XL

LUMAPHORE LED 600XL is a light tower equipped with a projector capable of delivering a maximum power of 520 W with which it can illuminate an area of 3200 m2.

It is appreciated in many industrial sectors:

- Road marking companies
- Asphalt paving crews
- Emergency services
- Civil defense
- Duct installers
- Highway companies

Main features of the LUMAPHORE LED 600XL:

Total lighting output: 520 W

Power supply output: 575 W

Protection index: IP65 / IK10

Wind resistance: 162 Km/h

Thermal protection: Yes

Temperature range for use: -15°/+40°

Lighting area: 3200 m2





Colour temperature: 5000 °K

Total lumens: 76200 lm

Colour rendering index: > 80

Diameter: 22.5 cm

Length: 91 cm

Weight: 7.7 kg

Tap type: Diameter: 26 mm

Optimum height for use: 4 m

Average assembly time: 2 min

Standard case: Included

Included Power cable (Schuko plug): 7 m

Suspension ring: Included

The advantages of LUMAPHORE:

- 3200 m² for 520 Watts
- Powerful floor lighting
- 100% immediate ignition
- Lightweight
- Sturdy: ABS, polycarbonate base, impact resistant PMMA diffuser
- Withstands harsh weather conditions
- Extremely multipurpose in its applications

Looking for a light tower with different characteristics? Access our dedicated area of light towers by clicking [here](#)

Images and technical data are not binding.

Product features:

Protection degree: IP65

Diameter (Ø): 22.5





Total lighting output (W): 520
Power of electricity supply (W): 575
Temperature range for use (°C): -15 / +40
Colour temperature (°K): 5000
Average assembly time (min): 2
Illuminated area (m²): 3200
Total lumens (Lm): 76200
Stability to wind (Km/h): 162
Length (mm): 910
Weight (Kg): 7.7

