



MECC ALTE ES16W-130 SINGLE PHASE ALTERNATOR 4,5 KVA

Product price:

261.00 € tax excluded

Product description:

MECC ALTE ES16W-130 SINGLEPHASE ALTERNATOR 4,5 KVA

The alternator MECC ALTE ES16W-130 single-phase, 2-pole is capable of delivering 4,5KVA continuous power complete with ASR voltage regulator.

MECC ALTE ES16W-130 alternators are designed to be exceptionally versatile, they are made to be suitable for all applications where an easy to carry power source is needed.

Mecc Alte portable alternators are available with a wide range of shafts, flanges and fittings. The 2-pole rotors have a damping cage and the stator windings have a reduced pitch to reduce harmonic content.

The alternator cover is die-cast from high-strength aluminum alloy, the shaft is C45 steel with splined fan. The degree of protection is IP23, the insulation is class H and the windings are impregnated with tropicalized epoxy resins.

MECC ALTE ES16W-130 single-phase alternators are designed without brushes and offer high operational reliability. As there are neither collectors nor sliding contacts, only a minimum of maintenance is required.

The MECC ALTE ES16W-130 alternator range is single phase AVR controlled, but designed with brushes and slip ring to allow good voltage regulation and better engine starting.

The purpose of the ASR is to keep the output voltage stable. Its operation is very simple, when resistive loads are fed, more complex is the matter in case of mainly inductive loads: the delayed current opposes the inductor magnetic field, causing a voltage drop at the alternator output terminals; to compensate the phenomenon, the AVR intervenes automatically increasing the excitation current, until the output returns to the nominal value.



TECHNICAL CHARACTERISTICS MECC ALTE ES16W-130

Phase type: Single-phase

Maximum singlephase power: 4,0 KW

Singlephase continuous use power: 3,2 KW Maximum singlephase power: 5,0 KVA

Singlephase continuous use power: 4,5 KVA

Frequency: 50 - 60 Hz

Voltage: 230 V

Degree of protection: IP21 Alternator speed: 3000 rpm

Number of poles: 2

Acoustic pressure: 72 dBA (56 dBA at 7 m)

Efficiency: 79.4%. Weight: 22,8 Kg

Constant speed alternator Voltage regulator: ASR

Are you looking for an alternator with different characteristics? <u>Here</u> you can find all MECC ALTE range and other specialized brands

Images and technical data are not binding and may be subject to manufacturer's revisions.

Product features:

Phase: Single phase

Maximum power single phase (KW): 4 Continuous power single phase (KW): 3.2 Maximum power single phase (KVA): 5 Continuous power single phase (KVA): 4.2

Frequency (Hz): 50 / 60

Voltage (V): 230

Engine rpm (rpm): 3000

Poles: 2

Single-phase power (KVA): 4.5

Efficiency (%): 79.4 Protection degree: IP21 Acoustic power: 72 dB(A)



Acoustic pressure: 56 dB(A) at 7 m

Brushes: Yes PMG: No

Type of alternator: Constant Speed

Voltage regulator: ASR Weight (Kg): 14.3

