



MECC ALTE ES16W-150 SINGLE PHASE ALTERNATOR 5,0 KVA

Product price:

269.00 € tax excluded

Product description:

MECC ALTE ES16W-150 SINGLEPHASE ALTERNATOR 5,0 KVA

The alternator MECC ALTE ES16W-150 single-phase, 2-pole is capable of delivering 5,0 KVA continuous power complete with ASR voltage regulator.

MECC ALTE ES16W-150 alternators are designed to be exceptionally versatile, they are made to be suitable for all applications where an easy to transport power source is needed.

Mecc Alte portable alternators are available with a wide range of shafts, flanges and fittings. The 2-pole rotors have a damping cage and the stator windings have a reduced pitch to reduce harmonic content.

MECC ALTE ES16W-150 single-phase alternators are designed without brushes and offer high operational reliability. As there are no collectors or sliding contacts, minimal maintenance is required.

The MECC ALTE ES16W-150 alternator range is single phase AVR controlled, but designed with brushes and slip ring to allow good voltage regulation and better engine starting.

The purpose of the ASR is to keep the output voltage stable. Its operation is very simple, when resistive loads are fed, more complex is the matter in case of mainly inductive loads: the delayed current opposes the inductor magnetic field, causing a voltage drop at the alternator output terminals; to compensate the phenomenon, the AVR intervenes automatically increasing the excitation current, until the output returns to the nominal value.

The series production meets the regulations and the essential safety requirements imposed by the European directive on electromagnetic compatibility; conformity to the latter is guaranteed by the application of European standards EN 61000-6-3, EN61000-6-2.



The alternators of the ES series comply with the EEC directives 2006/42, 2014/35, 2014/30, 2011/65, 2015/863 and relative modifications; therefore, they do not present any danger to the operator, if installed, used and maintained according to the instructions provided by Mecc Alte and provided that the safety devices are kept in perfect working order.

TECHNICAL CHARACTERISTICS MECC ALTE ES16W-150

Phase type: Single-phase
Maximum singlephase power: 4,8 KW
Singlephase continuous use power: 4,0 KW
Maximum singlephase power: 5,7 KVA
Singlephase continuous use power: 5,0 KVA
Frequency: 50 - 60 Hz
Voltage: 230 V
Degree of protection: IP21
Alternator speed: 3000 rpm
Number of poles: 2
Acoustic pressure: 72 dBA (56 dBA at 7 m)
Efficiency: 79,7%
Weight: 25,5 Kg
Constant speed alternator
Voltage regulator: ASR

Are you looking for an alternator with different characteristics? [Here](#) you can find all MECC ALTE range and other specialized brands

Images and technical data are not binding and may be subject to manufacturer's revisions.

Product features:

Phase: Single phase
Maximum power single phase (KW): 4.8
Continuous power single phase (KW): 4
Maximum power single phase (KVA): 5.7
Continuous power single phase (KVA): 5
Frequency (Hz): 50 / 60
Voltage (V): 230
Engine rpm (rpm): 3000
Poles: 2
Single-phase power (KVA): 5.7
Efficiency (%): 79.7
Protection degree: IP21
Acoustic power: 72 dB(A)



Acoustic pressure: 56 dB(A) at 7 m

Brushes: Yes

PMG: No

Type of alternator: Constant Speed

Voltage regulator: ASR

Weight (Kg): 14.3