



## TELWIN ENERGY 1500 START 230-400V 12-24V

## **Product description:**

TELWIN ENERGY1500 START CHARGER 230-400V 12-24V 7KW

Telwin Energy1500 Start is a 7KW battery charger and starter for charging free-electrolyte (WET) and lead-acid (START-STOP) batteries with a voltage of 12/24V.

The Telwin Energy1500 7KW battery charger allows quick starting of all types of cars, vans, light trucks, earth moving machines and trucks.

The Telwin charger gives the possibility to select 3 modes: normal, fast (BOOST) and finally quick start, according to the user's needs.

The Telwin Energy1500 is prepared for fast charging and equipped with a timer. Equipped with protection systems against both overloads and reverse polarity. Equipped with display for the visualization of the current charge and start-up. Equipped with remote control.

Telwin Energy1500 is a 7KW battery charger with a very high performance and it is very easy to carry and use thanks to the handle and the wheels that make it handy and easy to move. It is ideal both for the demanding hobbyist and for the professional, being a versatile, high performing and reliable product.

The Telwin Energy1500 battery charger has a voltage of 12/24V and its maximum starting current is 2000A and its charging power is 7KW. Its dimensions are 365x560x885mm and its weight is 69kg. The charger comes standard with two clamps, one ground and one positive, two 50 sq. mm. 3 m. long cables and a remote control.

TECHNICAL FEATURES OF THE 7KW TELWIN ENERGY1500 START BATTERY CHARGER

Type of phase: Single-phase/Three-phase Three phase mains voltage: 230 V/ 400V





Frequency: 50 / 60 Hz Charging power: 7 KW Starting power: 44 KW Charging voltage: 12 / 24 V

Effective charging current: 150 A /250 A

Charging current EN60335-2-29: 130 A / 220 A Starting current 1v/c EN60335-2-29: 1000 A / 1300 A

Maximum starting current: 1700 A / 2000 A

Rated capacity min ref: 70 Ah

Rated capacity ref.max: 2200 / 4000 Ah

Adjustment positions: 6

Length: 36.5 cm Width: 56 cm Height: 88.5 cm Weight: 69 Kg

Are you looking for a product with different characteristics? HERE you can find the entire range **TELWIN** and other specialized brands.

Images and technical data are not binding and subject to change by the manufacturer

## **Product features:**

Phase: Single phase / Three phase

Frequency (Hz): 50 / 60 Voltage (V): 230 / 400 Power (W): 44000

Effective current (A): 150 - 250

Adjustment positions: 6

Charging voltage (V): 12 / 24

Length (mm): 380 Width (mm): 560 Height (mm): 885 Dry weight (Kg): 69

Overload protectors: Yes

Video: 2I3AIIWsa3c