



# LINZ G-TS10C PTO UNIT 10KVA



## Product description:

LINZ G-TS10C 10KVA PTO shaft generator

LINZ G-TS10C 10KVA single-three phase PTO shaft generator with 430rpm tractor connection. The LINZ G-TS10C shaft-driven generator has a voltage of 230 / 400 V and a frequency of 50 Hz.

The E1S13S B/4 alternator of the LINZ G-TS10C PTO generator has a compound voltage regulator. The compound regulator allows you to stabilize the voltage and avoid damage to the connected sensitive devices.

The LINZ G-TS10C easy to transport, install and position due to its compact size, this model is ideal for mounting on a tractor unit. The LINZ G-TS10C shaft-driven generator has a tractor power requirement of 32 HP and a PTO speed of 430 rpm.

The LINZ G-TS10C has a tractor power requirement of 32 HP and a PTO speed of 430 rpm.

All alternators are equipped with an electrical panel including: Voltmeter, Ammeter, Frequency meter, CEE 5P socket, CEE 3P 16 or 32 Amp socket, Schuko socket with thermal protection, circuit breaker and residual current switch.

These compact gensets, robust and easy to use, are complete with a base with 3-point linkage for secure attachment to any tractor.

Power transmission is via cardan joint (not included), connected to the genset multiplier.

## Technical features of the LINZ G-TS10C:

Phase Type: Single Phase / Three Phase

Continuous Power: 10 KVA

Continuous Power: 10 KW

Voltage: 230 / 400 V





Frequency: 50 Hz  
PTO Power i output (rpm required 540): 17.6 HP  
Tractor power required: 32 HP  
PTO RPM: 430 rpm  
Alternator: E1S13S B/4  
Voltage regulator: Compound  
Length: 1152 mm  
Width: 960 mm  
Height: 1025 mm  
Weight: 165 Kg

Are you looking for a shaft generator with different technical characteristics? Here you can find the full range of LINZ cardan shaft generators or other brands specializing in this field.

Images and technical data are not binding and may be subject to manufacturer's revisions.

**Product features:**

Phase: Single phase / Three phase  
Continuous power single phase (KW): 10  
Maximum power single phase (KVA): 10  
Frequency (Hz): 50  
Voltage (V): 230 / 240  
Sockets configuration: CEE 5P, CEE 3P 16 o 32 Amp, Schuko  
PTO speed (round/min): 430  
Required tractor power: 32 HP  
Length (mm): 1152  
Width (mm): 960  
Height (mm): 1025  
Dry weight (Kg): 165  
Voltage regulator: Compound

