



PEDROLLO G-TL75 PTO UNIT 75KVA



Product price:

8.136,00 € tax excluded

Product description:

PEDROLLO G-TL75 75KVA PTO shaft generator

PEDROLLO G-TL75 75 KVA single-phase PTO shaft generator with 420rpm tractor connection. The PEDROLLO G-TL75 PTO generator has a voltage of 230 / 400 V and a frequency of 50 Hz.

The PEDROLLO G-TL75 is a tractor-driven PTO (power take-off) generator that includes a synchronous alternator, coupled to a speed increaser, towable from the tractor via a three-point hitch.

The PEDROLLO G-TL75 is easy to transport, install and position due to its compact size, this model is ideal for mounting on a tractor unit. The PEDROLLO G-TL75 PTO generator has a required tractor power of 180 HP and a PTO speed of 420 rpm.

The generator must be used after being placed on the ground. After connecting the tractor PTO to the gearbox via the PTO shaft, the tractor PTO must be set to the required speed.

The overgear, by transmitting the mechanical power of the tractor PTO to the alternator, increases the required PTO speed to the nominal speed of the alternator.

The PRO22 SB/4 alternator of the PEDROLLO G-TL75 PTO generator has an AVR voltage regulator. The voltage regulator, applied to synchronous current generators, has the objective of maintaining a constant operation of the machine, in its most efficient regime. Generally, this means maintaining the power factor at values close to 1, but if the synchronous machine is also used to phase other consumers in the same settlement, these values may vary.

D-AVR LINZ DR-30 (OPTIONAL)

The generators PEDROLLO G-TL75 can be equipped with the digital regulator DR30 that allows you to read conveniently from the dedicated App (available for Android)





and iOS) on your smartphone the following parameters:

- Frequency of the generator
- Chained voltages R-S-T
- Current, Cosphi, Active Power

Technical Features of the PEDROLLO G-TL75

Phase Type: Single Phase / Three Phase

Continuous Power: 75 KVA

Continuous Power: 65 KW

Voltage: 230 / 400 V

Frequency: 50 Hz

PTO Power i output (rpm required 540): 98. 7 HP

Tractor power required: 180 HP

PTO RPM: 420 rpm

Alternator: PRO22 SB/4

Voltage controller: AVR

Length: 1356 mm

Width: 1092 mm

Height: 1138 mm

Weight: 494 Kg

Are you looking for a shaft generator with different technical features? Here you can find the full range of PEDROLLO cardan shaft generators and other brands specializing in this field.

Images and technical data are not binding and may be subject to manufacturer's revisions.

Product features:

Phase: Single phase / Three phase

Continuous power single phase (KW): 65

Maximum power single phase (KVA): 75

Frequency (Hz): 50

Voltage (V): 230 / 240

Sockets configuration: CEE 5P, CEE 3P 16 o 32 Amp, Schuko

PTO speed (round/min): 420

Required tractor power: 180 HP

Length (mm): 1356

Width (mm): 1092

Height (mm): 1138





Dry weight (Kg): 494.5

Voltage regulator: AVR