



AIRSTAR SIROCCO 2M 1x2500 HMI

Product description:

AIRSTAR SIROCCO 2M 1x2500 HMI

AIRSTAR SIROCCO 2M 1x2500 HMI is a lightglobe equipped with HMI lamp capable of delivering a total light output of 2500W, thanks to which it can illuminate an area of 7250 m².

The AIRSTAR SIROCCO 2M Lightglobe is a perfect lighting device for night work and on-site interventions. The lamps HMI (Hydrargyrum Medium-arc Iodide) is able to illuminate in daylight a very large area, in addition has been designed to be, are intense lights, with a typical efficiency of 60-80 lumens per watt and anti-glare system.

The AIRSTAR SIROCCO 2M lightglobe is completely waterproof and can also be used in wet working environments or in the presence of water, giving you the possibility to always work with maximum safety.

AIRSTAR SIROCCO 2M 1x2500 HMI comes complete with a telescopic pole made of chrome-plated steel that is resistant to corrosion and rust. The telescopic pole can reach a height of 6.60 m and can support a maximum weight of 50 kg, in addition it gives a very good stability to the lightglobe even in unfavorable conditions with wind up to 100 Km/h.

TECHNICAL FEATURES AIRSTAR SIROCCO 2M 1x2500 HMI:

Envelope diameter: 140 cm

Envelope height: 70 cm

Maximum pole height: 6.60 m

Color temperature: 5500 - 6500 K

Number of lamps: 1

Lamp type: HMI

Lamp power: 2500 W

Power supply (50 Hz): 207 V



Power supply (60 Hz): 220 - 240 V

Lighting area for activities at the first risk level (standard EN12464-2): 1350 m²

Lighting area open space environment (standard EN1838): 7250m².

Lighting under the balloon (placed at 3 meters): 1700 Lx

Luminous flux: 240000Lm

Global protection class: IP 54

Open dimension: Ø 2000 x 6600 mm

Balloon weight: 10 Kg

Ballast weight: 25 Kg

Telescopic pole weight: 23 Kg

Looking for a Lightglobe with different technical features? Here you can find the full range of Lightglobe AIRSTAR or other specialized brands.

Images and technical data not binding.

Product features:

Frequency (Hz): 50 / 60

Voltage (V): 207 (50 Hz) / 220 - 240 (60 Hz)

Protection degree: IP54

Type of lamps: HMI

Lamps: 1 x 2500 W

Telescopic pole: Acciaio cromato

Illuminated area (m²): 7250

Total lumens (Lm): 240000

Maximum height (m): 6.6

Open size (mm): Ø 2000 x 6600

Weight (Kg): 58

Video: f75VOHNRwkQ

