



AIRSTAR FLEX M HTI 1X1000W

Product description:

AIRSTAR FLEX M HTI 1X1000W

AIRSTAR FLEX M HTI 1X1000W is a lightglobe equipped with an HTI lamp capable of delivering a total light output of 1000W, thanks to which it can illuminate an area of 4700 m².

The Lightglobe AIRSTAR FLEX M HTI 1X1000W is a perfect lighting device for night work and onsite operations. The HTI Lamps (Hydrargyrum Tageslicht Iodide) is able to illuminate by day a very large area, in addition it is designed to be, intense lights, are short arc lamps with maximum luminance and anti-glare system.

AIRSTAR FLEX M HTI 1X1000W comes complete with telescopic pole made of corrosion and rust resistant chromed steel. The telescopic pole can reach a height of 5.30 m and can support a maximum weight of 40 kg, in addition to giving excellent stability to the lightglobe even in unfavorable conditions with winds up to 100 Km / h.

AIRSTAR FLEX M HTI 1X1000W is supplied with a chrome-plated steel pole resistant to corrosion and rust.

TECHNICAL FEATURES AIRSTAR FLEX M HTI 1X1000W:

Envelope diameter: 120 cm Envelope height: 70 cm

Maximum pole height: 5. 30 m Color temperature: 4000 K

Number of lamps: 1 Type of lamps: HTI Lamp power: 1000 W Frequency: 50 Hz





Power supply voltage: 220 - 240 V

Lighting area for activities at the first level of risk (standard EN12464-2): 870 m²

Lighting area open space environment (standard EN1838): 4700 m².

Lighting under the balloon (placed at 7 meters): 780 Lx

Luminous flux: 110000 Lm Global protection class: IP 54 Open size: Ø 1650 x 5300 mm

Balloon weight: 10 Kg

Telescopic pole weight: 16 Kg

Looking for a Lightglobe with different technical features? Here you can find the full range of Lightglobe AIRSTAR or other specialized brands.

Images and technical data not binding.

Product features:

Frequency (Hz): 50 Voltage (V): 220 - 240 Protection degree: IP54

Type of lamps: Htl Lamps: 1 x 1000 W

Telescopic pole: Acciaio cromato

Illuminated area (m²): 4700 Total lumens (Lm): 110000 Maximum height (m): 5.3

Open size (mm): Ø 1650 x 5300

Video: 1bZH1bIIPWA

