



NANNI QMS25M MARINE GENERATOR 25KVA

Product description:

NANNI QMS25M MARINE GENERATOR 25KVA

NANNI QMS25M is a single-phase marine generator equipped with a Kubota 4-stroke diesel engine capable of delivering a maximum power of 25KVA.

The NANNI QMS25M generator is equipped with a fast heating injector and glow plug and are positioned in the combustion chamber, ensuring engine start-up even at low temperatures.

The cooling system allows the NANNI QMS25M to operate at an optimal temperature. In the case of closed loop heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. The Super Glow system comes as standard equipment for cold weather starting.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS25M is improved, resulting in low fuel consumption.

NANNI QMS25M is complete with freshwater and saltwater exchanger. Also available with a keel cooling system, also known as Keel Cooling.

The NANNI QMS25M's alternator provides 20KW of power in continuous operation and can produce up to 23KW. Protection level IP23 (protection level available on request).

TECHNICAL FEATURES NANNI QMS25M

Maximum output: 23 KW

Continuous use output: 20 KW

Maximum output: 27.5 KVA

Continuous use output: 25 KVA

Fuel: Diesel



Voltage: 230 V
Frequency: 50 Hz
Engine: Kubota, 4 strokes
Starting: Electric
Insulation class: H
Protection class: IP23
Consumption: 8.2 Lt/h at full load
Length: 1590 mm
Width: 750 mm
Height: 900 mm
Weight: 550 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase
Maximum power single phase (KW): 23
Continuous power single phase (KW): 20
Maximum power single phase (KVA): 27.5
Continuous power single phase (KVA): 25
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Engine: Kubota, 4 stroke
Engine rpm (rpm): 1500
Starting system: Electric
Number cylinders: 4
Cylinders' position: In line
Cooling: Water
Inyección : Indirect (E-TVCS)
Alternator: Electronic regulator
Consumption (L/h): 8.2 at 100% of the load
Length (mm): 1590
Width (mm): 750
Height (mm): 900



Dry weight (Kg): 550