



NANNI QMS46T MARINE GENERATOR 46KVA



Product description:

NANNI QMS46T MARINE GENERATOR 46KVA

NANNI QM462T is a three-phase marine generator equipped with a Kubota engine, 4-stroke with Diesel power supply capable of delivering a maximum power of 46KVA.

The cooling system allows the NANNI QMS46T to operate at an optimal temperature. In the case of closed circuit heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. The NANNI QMS46T marine generator is equipped with the Super Glow system for starting in cold temperatures without the risk of sudden engine failure.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS46T is improved, resulting in low fuel consumption.

The alternators used in the QMS range are manufactured by Mecc Alte, a world leader in the production of compact synchronous alternators. All NANNI QMS generators feature an acoustic enclosure consisting of insulated panels of painted marine aluminum, with multiple access doors for all necessary connections and maintenance items, including visual lifting access.

NANNI QMS46T TECHNICAL SPECIFICATIONS

Phase Type: Three Phase

Maximum Power: 37.8 KW

Continuous Power: 34.4 KW

Maximum Power: 45.9 KVA

Continuous Power: 41.8 KVA

Fuel: Diesel

Voltage: 400 V





Frequency: 50 Hz
Engine: Kubota, 4-stroke
Start: Electric
Isolation Class: H
Protection Class: IP23
Consumption: 6.9 Lt/h at full load
Length: 1590 mm
Width: 700 mm
Height: 900 mm
Weight: 670 kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Three phase
Maximum power three phase (KW): 37.8
Continuous power three phase (KW): 34.4
Maximum power three phase (KVA): 45.9
Continuous power three phase (KVA): 41.8
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 400
Engine: Kubota, 4 stroke
Engine rpm (rpm): 1500
Starting system: Electric
Number cylinders: 4
Cylinders' position: In line
Cooling: Water
Inyección : Indirect (E-TVCS)
Alternator: Electronic regulator
Protection degree: IP23
Motor insulation class: H
Consumption (L/h): 8.2 at 100% of the load
Length (mm): 1590
Width (mm): 700





Height (mm): 900
Dry weight (Kg): 670
Silenced: Yes