



# NANNI QMS16M MARINE GENERATOR 16.2KW

## Product description:

### NANNI QMS16M MARINE GENERATOR 16.2KW

NANNI QMS16M is a three-phase marine generator equipped with a Kubota 4-stroke engine with Diesel power supply capable of delivering a maximum power of 16.2KW.

The NANNI QMS16M is equipped with a Kubota base engine which has been used for years in marine and industrial applications all over the world.

The NANNI QMS16M generator is equipped with a fast-heating injector and glow plug and are located in the combustion chamber, ensuring that the engine will start even at low temperatures.

The cooling system allows the NANNI QMS16M to operate at an optimal temperature. In the case of closed-loop heat exchanger cooling, the coolant is cooled by seawater flowing through the heat exchanger.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS16M is improved, resulting in low fuel consumption.

NANNI QMS16M is complete with freshwater and saltwater exchanger. Also available with a keel cooling system, also known as Keel Cooling.

The NANNI QMS16M's alternator provides 13.9 KW of power in continuous operation and can produce up to 16.2 KW. Protection level IP23 (protection level available on request).

## TECHNICAL FEATURES NANNI QMS16M

Maximum power Single-phase: 16.2 KW

Single-phase continuous use power: 13.9 KW





Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Engine: Kubota, 4 stroke  
Starting: Electric  
Consumption: 4.8 Lt/h at full load  
Length: 1014 mm  
Width: 548 mm  
Height: 691 mm  
Weight: 328 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 16.2  
Continuous power single phase (KW): 13.9  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Kubota, 4 stroke  
Engine rpm (rpm): 1500  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 2197  
Number cylinders: 4  
Cylinders' position: In line  
Oil capacity (L): 7.5  
Cooling: Water  
Inyección : Indirect (E-TVCS)  
Alternator: Electronic regulator  
Bore x stroke (mm): 87 x 92.4  
Consumption (L/h): 4.8 at 100% of the load  
Length (mm): 1014  
Width (mm): 548  
Height (mm): 691





Dry weight (Kg): 328

Silenced: No