



WEBASTO SOD PURE TYP-2 7.0 22KW ELECTRIC CAR CHARGING STATION

Product price:

830,00 € tax excluded

Product description:

WEBASTO SOD PURE TYP-2 7.0 ELECTRIC CAR CHARGING STATION 22KW

WEBASTO SOD PURE is a charging station for electric cars capable of delivering a maximum charging power of 22 KW with 12 RGB LED display and auto power off when charging is complete.

With WEBASTO SOD PURE you can have the convenience of an electric car charging station directly under your home. WEBASTO SOD PURE is the safest and most careful solution for your vehicle battery. In this way you will have both the security of having your electric car ready every day, and thanks to a stable and continuous charge you will ensure a long battery life.

The WEBASTO SOD PURE electric car station boasts high charging power, maximum safety and maximum convenience. Charging with a WEBASTO SOD PURE is up to 10 times faster than a typical household outlet and automatically stops as soon as the battery is charged.

Technical Specifications WEBASTO SOD PURE:

Rated Current (A): 8, 10, 13, 16, 20, 25, 32

Phase type: Three-phase, Single-phase, Two-phase

Mains voltage: 230/400 V (European)

Mains frequency: 50 Hz

Overvoltage category: III in accordance with EN 60664

Protection class: I

Cable length: 7.0 m

Device of protection: IP54

Protection against mechanical impact: IK08

Output voltage: 230 / 400 Vac



Max. charging power: 22 KW
Display: 12 RGB LEDs, buzzer
Locking mechanism Universal key switch
Width: 225 mm
Depth: 116 mm
Height: 447 mm
Weight: 7 Kg

WEBASTO station impresses with its many advantages:

- Power capacity of 22 kW, 7.0 m cable (more options to come)
- Up to ten times faster than using a standard household outlet
- Simple and convenient operation
- Safe operation including protective measures
- High quality engineering
- Affordable price and expert technical support
- High quality "Made in Germany"

If you are looking for a Webasto charging station or similar products then you can browse our entire catalogue.

Images and technical data are not binding.

Product features:

Phase: Three Phase, Single Phase, Two Phase
Maximum power single phase (KW): 22
Maximum power three phase (KW): 22
Frequency (Hz): 50
Voltage (V): 230 / 400
Protection degree: IP54
Nominal current (A): 8, 10, 13, 16, 20, 25, 32
Length (mm): 116
Width (mm): 225
Height (mm): 447
Weight (Kg): 7
Overvoltage category: III in accordance with EN 60664
Safety standards: Conforms to EN 61140
Network systems: TT/TN
EMC class: Interference emission: Class B (residential, commercial, industrial areas) Interference resistance: industrial areas





Assembly: Wall or stand mounting

Power cable: Mounted on-wall or in-wall

Cross section of the connection (cable dimensions): Minimum cross-section (depending on cable and installation type): - 5 x 2.5 mm² (16 A rated current) - 5 x 6.0 mm² (32 A rated current)

Charging cable: Type 2 in accordance with EN 62196-1 and EN 62196-2 up to 32 A / 400 V AC; 4.5 m long, integrated cable bracket

Output voltage (VAC): 230 / 400

Max. charging capacity (KW): 22

Mechanical locking: Key switch to allow charging to begin

Display: 16 RGB LEDs, Buzzer

Protection against mechanical impact: IK7

Operating temperature range (°C): From -25 to +55

Operating temperature range (°C): From -25 to +80

Permissible relative humidity (%): From 5 to 95 without condensation

Altitude (m): Max 3000 m above sea level

