



# MOSA GE 7000 KBM SINGLE PHASE GENERATOR 6,7KVA STAGE V

### **Product price:**

1.022,48 € tax excluded

#### **Product description:**

MOSA GE 7000 KBM SINGLE-PHASE GENERATOR 6.7KVA STAGE V

MOSA GE7000 KBM is a single-phase generating set with a gasoline-powered engine capable of delivering a power of 6KW. The MOSA GE7000 KBM generating set is equipped with manual recoil starter. The MOSA GE7000 KBM generator set alternator is synchronous, single phase, self-excited, self-regulated, brushless and with class H insulation.

MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 76 kg as well as its practical tubular handles.

The MOSA GE7000 KBM generator set with 6.1-liter tank has a fuel consumption of 2.4 liters/hour at 75% load for an autonomy of up to 2 hours.

The control panel is composed of:

- Output sockets: 1x 230V 32A 2P+E CEE / 1x 230V 16A 2P+E CEE
- Thermal circuit breaker for socket protection 230V/16A
- Voltmeter
- Thermomagnetic circuit breaker
- Earth terminal (PE)

## **Technical specifications MOSA GE7000 KBM:**

Single-phase continuous use power: 5 KW Single-phase continuous use power: 5.5 kVA

Maximum single-phase power: 6 KW Maximum single-phase power: 6.7 kVA

Fuel: Gasoline Voltage: 230 V





Frequency: 50 Hz

Motor: KOHLER CH440 Start: Manual Rewind

Consumption: 2. 4 Lt/h at 75% load

Acoustic power measured LwA: 97 dB(A) (71 dB(A) @ 7m)

Length: 770 mm Width: 520 mm Height: 650 mm Weight: 76 Kg

If you are looking for another product like the MOSA GE7000 KBM generator set then you can check out our catalog for other land based generator sets.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase

Maximum power single phase (KW): 6 Continuous power single phase (KW): 5 Maximum power single phase (KVA): 6.7 Continuous power single phase (KVA): 5.5

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 230V 16A 2P+T CEE - 1 x 230V 16A 2P+T SCHUKO

Engine: KOHLER CH440

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Speed governor: Mechanical

Ignition: Recoil

Starting system: Pull starter Engine capacity (cm³): 389

Number cylinders: 1 Oil capacity (L): 1.1

Cooling: Air

Alternator: Synchronous self-excited, self-regulated, brushless

Bore x stroke (mm): 88 x 64 Compression ratio: 8.2 : 1

Length (mm): 770 Width (mm): 520 Height (mm): 650 Dry weight (Kg): 76





Silenced: No

ATS Switch device : No Voltage regulator: Capacitor Engine manufacturer: Kohler

